


**↳19" Rack Mounted Sure Protection Panel**

- 12, 24 or 48 Port Configurations
- Supports All Network Types
- RJ45 on Front and 110 Block on Rear
- Designed for Individual Port Replacement
- UL497B Listed

Electrical Characteristics		
Max. DC operating voltage	Uc	7.5 Vdc
Insertion loss		< 1 dB
Max. load current @25°C	IL	750 mA
Max. capacitance	C	< 8 pF
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	500 A
Capacity Maximum	pF	<8
Telecom Discharge Current 10/1000	kA	0,1
Telecom Total Discharge Current 10/1000	kA	0,1
Telecom Discharge Current 10/1000	kA	0,1
Telecom Discharge Current 10/1000	kA	0,1
Option		
RFI Filter		no
Installation		
Wiring type		Shielded RJ45
Operating Temperature <sub>Min</sub>	°C	-40.0000
Operating Temperature <sub>Max</sub>	°C	85.0000
Operating Temperature <sub>Min</sub>	°F	-40.0000
Operating Temperature <sub>Max</sub>	°F	85.0000
Operating Relative Humidity <sub>Max</sub>	%RH	95
Operating Altitude <sub>Min</sub>	Ft	2000.0000
Operating Altitude <sub>Max</sub>	Ft	6500.0000
Housing/Enclosure material		Aluminum
Mounting		19" Rack
IP Environmental rating <sub>IP</sub>		IP20
NEMA Environmental rating <sub>NEMA</sub>		NEMA 1
Installation Location		Indoor
Product Dimension <sub>H</sub>	mm	89.0000
Product Dimension <sub>W</sub>	mm	483.0000
Product Dimension <sub>H</sub>	In	3.5000
Product Dimension <sub>W</sub>	In	19.0000
Miscellaneous		
Individual Pack		Yes
Storage Temperature <sub>Min</sub>	°C	-40.0000
Storage Temperature <sub>Max</sub>	°C	85.0000
Storage Temperature <sub>Min</sub>	°F	-40.0000
Storage Temperature <sub>Max</sub>	°F	85.0000
Storage Relative Humidity <sub>Max</sub>	%RH	95.0000
Installation		
Cable type		Ethernet
Mechanical Characteristics		
Connection to Network		Self-stripping connector 110 back/RJ45 Female. front
Weight		0.3 kg
Part number		
6249		