



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x 8/20us)
- 5kA I_{mp} (2x 10/350us)
- 5kA I_n (10x 8/20us)
- Modular
- 2W+SHIELD+G

	<table border="1"> <thead> <tr> <th colspan="2">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Max. DC operating voltage</td> <td>U_c 15 Vdc</td> </tr> <tr> <td>Insertion loss</td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL 2.4 A</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>I_{imp} 5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td> <td>I_n L/PE 5 kA</td> </tr> <tr> <td>DATA SPD TYPE</td> <td>UL497B LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V) 12</td> </tr> <tr> <td>WIRES</td> <td>2W+SHIELD+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A) 2.4</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C) -50</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C) +85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V) 30</td> </tr> <tr> <td>MCOV</td> <td>(V) 28</td> </tr> <tr> <td>IN 10 impulses 8/20µs</td> <td>(kA) 5</td> </tr> <tr> <td>IMAX 8/20µs</td> <td>(kA) 20</td> </tr> <tr> <td>I_{imp} 10/350µs</td> <td>(kA) 5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps) 10/100</td> </tr> <tr> <td>INSERTION LOSS (@ FREQ)</td> <td>(db) < 1</td> </tr> </tbody> </table>	Electrical Characteristics		Max. DC operating voltage	U _c 15 Vdc	Insertion loss	< 1 dB	Max. load current @25°C	IL 2.4 A	Impulse current 2 x 10/350µs Test - D1 Category	I _{imp} 5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I _n L/PE 5 kA	DATA SPD TYPE	UL497B LISTED	VOLTS	(V) 12	WIRES	2W+SHIELD+G	LINE CURRENT MAX	(A) 2.4	AMBIENT MIN	(C) -50	AMBIENT MAX	(C) +85	RESIDUAL VOLTAGE	(V) 30	MCOV	(V) 28	IN 10 impulses 8/20µs	(kA) 5	IMAX 8/20µs	(kA) 20	I _{imp} 10/350µs	(kA) 5	DATA SPEED	(Mbps) 10/100	INSERTION LOSS (@ FREQ)	(db) < 1
Electrical Characteristics																																							
Max. DC operating voltage	U _c 15 Vdc																																						
Insertion loss	< 1 dB																																						
Max. load current @25°C	IL 2.4 A																																						
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp} 5 kA																																						
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I _n L/PE 5 kA																																						
DATA SPD TYPE	UL497B LISTED																																						
VOLTS	(V) 12																																						
WIRES	2W+SHIELD+G																																						
LINE CURRENT MAX	(A) 2.4																																						
AMBIENT MIN	(C) -50																																						
AMBIENT MAX	(C) +85																																						
RESIDUAL VOLTAGE	(V) 30																																						
MCOV	(V) 28																																						
IN 10 impulses 8/20µs	(kA) 5																																						
IMAX 8/20µs	(kA) 20																																						
I _{imp} 10/350µs	(kA) 5																																						
DATA SPEED	(Mbps) 10/100																																						
INSERTION LOSS (@ FREQ)	(db) < 1																																						
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube L: Inductor D: Clamping diode</p>	<table border="1"> <thead> <tr> <th colspan="2">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Connection to Network</td> <td>By screw terminal: cross section 0.4-1.5mm²</td> </tr> <tr> <td>TECHNOLOGY</td> <td>SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td>1 pair</td> </tr> <tr> <td>CONNECTION METHOD</td> <td>Screw Terminal</td> </tr> <tr> <td>MOUNTING</td> <td>DIN RAIL</td> </tr> <tr> <td>MATERIAL</td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td>DLAHM-12D3</td> </tr> </tbody> </table>	Mechanical Characteristics		Connection to Network	By screw terminal: cross section 0.4-1.5mm ²	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 pair	CONNECTION METHOD	Screw Terminal	MOUNTING	DIN RAIL	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAHM-12D3																
Mechanical Characteristics																																							
Connection to Network	By screw terminal: cross section 0.4-1.5mm ²																																						
TECHNOLOGY	SAD-GDT																																						
NETWORK CONFIGURATION	1 pair																																						
CONNECTION METHOD	Screw Terminal																																						
MOUNTING	DIN RAIL																																						
MATERIAL	Thermoplastic UL94-V0																																						
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																						
DIMENSIONS	See diagram																																						
WEIGHT	0.30 lbs																																						
SPARE PART	DLAHM-12D3																																						
	<table border="1"> <thead> <tr> <th colspan="2">Standards</th> </tr> </thead> <tbody> <tr> <td>UL STANDARD</td> <td>UL497B</td> </tr> <tr> <td>UL CATEGORY</td> <td>QVGQ</td> </tr> <tr> <td>UL FILE NUMBER</td> <td>E184939</td> </tr> <tr> <td>STANDARDS</td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td>ROHS</td> </tr> </tbody> </table> <p>Part number 641002</p>	Standards		UL STANDARD	UL497B	UL CATEGORY	QVGQ	UL FILE NUMBER	E184939	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																										
Standards																																							
UL STANDARD	UL497B																																						
UL CATEGORY	QVGQ																																						
UL FILE NUMBER	E184939																																						
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																						
ENVIRONMENTAL STANDARDS	ROHS																																						

