



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x 8/20us)
- 5kA I_{mp} (2x 10/350us)
- 10kA I_n (10x 8/20us)
- Modular
- 4W+SHIELD+G



	Electrical Characteristics	
	Network	RS422
	Max. DC operating voltage	U _c 8 Vdc
	Max. frequency	f max. > 3 MHz
	Max. load current @25°C	I _L 300 mA
	Impulse current 2 x 10/350µs Test - D1 Category	I _{imp} 5 kA
	Nominal discharge current C2 Category	I _n 5 kA
	Line resistance (± 10%)	4.7 Ohm
	DATA SPD TYPE	UL497B LISTED
	VOLTS (V)	6
	WIRES	4W+SHIELD+GROUND
	LINE CURRENT MAX (A)	0.3
	AMBIENT MIN (C)	-50
	AMBIENT MAX (C)	+85
	RESIDUAL VOLTAGE (V)	20
	MCOV (V)	8/72/72
	I _{MAX} 8/20µs (kA)	20
	I _{imp} 10/350µs (kA)	5
	DATA SPEED (Mbps)	up to 10MHz
	FREQUENCY (MHz)	up to 10
	INSERTION LOSS (@ FREQ) (db)	< 1
	CAPACITANCE (pF)	< 50
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	Mechanical Characteristics	
	Technology	GDT+Clamping diode
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²	
Format	Plug-in DIN box	
Operating and storage temperature	-40/+85°C	
Failsafe mode	Short-circuit	
TECHNOLOGY	SAD-GDT	
NETWORK CONFIGURATION	2 Channel (4W+SHIELD+G)	
CONNECTION METHOD	Screw Terminal	
MOUNTING	Din Rail	
MATERIAL	Thermoplastic UL94-V0	
NEMA RATING (IP RATING)	NEMA 2 (IP20)	
DIMENSIONS	See diagram	
WEIGHT	0.30 lbs	
SPARE PART	DLA2M-06D3	
Standards		
Certification	UL Listed	
UL STANDARD	UL497B	
UL CATEGORY	QVGQ	
UL FILE NUMBER	E184939	
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	
ENVIRONMENTAL STANDARDS	ROHS	
Part number		
640111		

