



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x-8/20us)
- 5kA I_{mp} (2x-10/350us)
- 5kA I_n (10x-8/20us)
- Modular
- 2W+SHIELD+G



<p>65 13 90 DINRAIL 3a 4a 1a 2a 1b 2b 3b 4b</p>	Electrical Characteristics																																																																
<p>1a 1b 2a 2b 4a 4b 3a 3b earth possible on DIN rail</p> <p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Max. DC operating voltage</td><td>U_c</td><td>53 Vdc</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Impulse current 2 x 10/350µs Test - D1 Category</td><td>I_{imp}</td><td>5 kA</td></tr> <tr><td>Nominal discharge current C2 Category</td><td>I_n</td><td>5 kA</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL497B LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>48</td></tr> <tr><td>WIRES</td><td></td><td>2W+Shield+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-40</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>70</td></tr> <tr><td>MCOV</td><td>(V)</td><td>60</td></tr> <tr><td>IN</td><td>(kA)</td><td>5</td></tr> <tr><td>10 impulses 8/20µs</td><td></td><td></td></tr> <tr><td>IMAX 8/20µs</td><td>(kA)</td><td>20</td></tr> <tr><td>I_{imp} 10/350µs</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>FREQUENCY</td><td>(MHz)</td><td>up to 10</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>< 1</td></tr> <tr><td>CAPACITANCE</td><td>(pF)</td><td>< 50</td></tr> </table>		Max. DC operating voltage	U _c	53 Vdc	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA	Nominal discharge current C2 Category	I _n	5 kA	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	48	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	70	MCOV	(V)	60	IN	(kA)	5	10 impulses 8/20µs			IMAX 8/20µs	(kA)	20	I _{imp} 10/350µs	(kA)	5	DATA SPEED	(Mbps)	10/100	FREQUENCY	(MHz)	up to 10	INSERTION LOSS (@ FREQ)	(db)	< 1	CAPACITANCE	(pF)	< 50
Max. DC operating voltage	U _c	53 Vdc																																																															
Insertion loss		< 1 dB																																																															
Max. load current @25°C	IL	300 mA																																																															
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA																																																															
Nominal discharge current C2 Category	I _n	5 kA																																																															
DATA SPD TYPE		UL497B LISTED																																																															
VOLTS	(V)	48																																																															
WIRES		2W+Shield+G																																																															
LINE CURRENT MAX	(A)	0.3																																																															
AMBIENT MIN	(C)	-40																																																															
AMBIENT MAX	(C)	+85																																																															
RESIDUAL VOLTAGE	(V)	70																																																															
MCOV	(V)	60																																																															
IN	(kA)	5																																																															
10 impulses 8/20µs																																																																	
IMAX 8/20µs	(kA)	20																																																															
I _{imp} 10/350µs	(kA)	5																																																															
DATA SPEED	(Mbps)	10/100																																																															
FREQUENCY	(MHz)	up to 10																																																															
INSERTION LOSS (@ FREQ)	(db)	< 1																																																															
CAPACITANCE	(pF)	< 50																																																															
	Mechanical Characteristics																																																																
	<table border="1"> <tr><td>Connection to Network</td><td colspan="2">By screw terminal: cross section 0.5-2.5mm²</td></tr> <tr><td>TECHNOLOGY</td><td colspan="2">SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td colspan="2">1 Channel (2W+SHIELD+G)</td></tr> <tr><td>CONNECTION METHOD</td><td colspan="2">Screw terminal</td></tr> <tr><td>MOUNTING</td><td colspan="2">Din rail</td></tr> <tr><td>MATERIAL</td><td colspan="2">Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td colspan="2">NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td colspan="2">See diagram</td></tr> <tr><td>WEIGHT</td><td colspan="2">0.30 lbs</td></tr> <tr><td>SPARE PART</td><td colspan="2">DLAM-48D3</td></tr> </table>		Connection to Network	By screw terminal: cross section 0.5-2.5mm ²		TECHNOLOGY	SAD-GDT		NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)		CONNECTION METHOD	Screw terminal		MOUNTING	Din rail		MATERIAL	Thermoplastic UL94-V0		NEMA RATING (IP RATING)	NEMA 2 (IP20)		DIMENSIONS	See diagram		WEIGHT	0.30 lbs		SPARE PART	DLAM-48D3																																		
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																																																																
TECHNOLOGY	SAD-GDT																																																																
NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)																																																																
CONNECTION METHOD	Screw terminal																																																																
MOUNTING	Din rail																																																																
MATERIAL	Thermoplastic UL94-V0																																																																
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																																																
DIMENSIONS	See diagram																																																																
WEIGHT	0.30 lbs																																																																
SPARE PART	DLAM-48D3																																																																
	Standards																																																																
	<table border="1"> <tr><td>Certification</td><td colspan="2">UL Listed</td></tr> <tr><td>UL STANDARD</td><td colspan="2">UL497B</td></tr> <tr><td>UL CATEGORY</td><td colspan="2">QVGQ</td></tr> <tr><td>UL FILE NUMBER</td><td colspan="2">E184939</td></tr> <tr><td>STANDARDS</td><td colspan="2">IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td colspan="2">ROHS</td></tr> </table>		Certification	UL Listed		UL STANDARD	UL497B		UL CATEGORY	QVGQ		UL FILE NUMBER	E184939		STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993		ENVIRONMENTAL STANDARDS	ROHS																																														
Certification	UL Listed																																																																
UL STANDARD	UL497B																																																																
UL CATEGORY	QVGQ																																																																
UL FILE NUMBER	E184939																																																																
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																																
ENVIRONMENTAL STANDARDS	ROHS																																																																
	Part number																																																																
	6403021																																																																

