



- ↳ UL Type 1 CA DC SPD
- VG Technology for Maximum Performance
- Zero Leakage Current
- Zero Current Working
- Iimp : 12.5kA/pole at 10/350µs
- In:20kA/pole at 8/20µs
- UL 1449 5th Edition Recognized



Electrical Characteristics		
Total Maximum discharge current <i>max. total withstand @ 8/20 µs</i>	I _{max} Total	60 kA
Protection mode(s)		Common/Differential mode
Protection level +/PE (-/PE) <i>@ I_n (8/20µs)</i>	U _p	2.5 kV
Maximum Discharge Current <i>I_{max} (8/20)</i>	kA	40.0000
Maximum Discharge Current <i>I_{max} (8/20)</i>	kA	40.0000
Maximum Discharge Current <i>I_{max} (8/20)</i>	kA	40.0000
POWER SPD TYPE		UL1449 TYPE 1CA
VOLTS	(V)	500
AC/DC/DC PV/RF		DC PV
PHASE	(PH)	-
AMPS	(A)	N/A
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+85
MODES		DC+G or DC-G
VPR	(V)	2500/1500/1500
MCOV	(V)	500/500/500
IN <i>15 impulses 8/20µs</i>	(kA)	20
SCCR	(kA)	100
Option		
Remote status dry contact electrical rating <i>Max Voltage</i>	V	250.0000
Remote status dry contact electrical rating <i>Max Current</i>	A	0.5000
RFI Filter		no
Installation		
Wiring type		Screw
Solid wire cross section <i>Min</i>	mm ²	4.0000
Solid Wire cross section <i>Max</i>	mm ²	25.0000
Stranded Wire cross section <i>Min</i>	mm ²	4.0000
Stranded wire cross section <i>Max</i>	mm ²	25.0000
Wire gauge <i>Min</i>	AWG	12.0000
Wire gauge <i>Max</i>	AWG	4.0000
Torque	Nm	2.0 - 2.5
Torque	in-lbs	17.8 - 22.1
Strip Length	mm	12.5000
Strip Length	in	0.5000
Operating Temperature <i>Min</i>	°C	-40.0000
Operating Temperature <i>Max</i>	°C	85.0000
Operating Temperature <i>Min</i>	°F	-40.0000
Operating Temperature <i>Max</i>	°F	85.0000
Operating Relative Humidity <i>Max</i>	%RH	95
Operating Altitude <i>Min</i>	Ft	2000.0000
Operating Altitude <i>Max</i>	Ft	6500.0000
Housing/Enclosure material		Thermoplastic
Flammability rating <i>UL 94</i>		V0
Mounting		Din Rail
IP Environmental rating <i>IP</i>		IP20
NEMA Environmental rating <i>NEMA</i>		NEMA 1
Installation Location		Indoor
Spare part		Module
Product Dimension <i>L</i>	mm	99.0000
Product Dimension <i>H</i>	mm	67.0000

Product Dimension <i>W</i>	mm	54.0000
Product Dimension <i>L</i>	In	3.8900
Product Dimension <i>H</i>	In	2.6400
Product Dimension <i>W</i>	In	2.1300
Miscellaneous		
Individual Pack		Yes
Storage Temperature <i>Min</i>	°C	-40.0000
Storage Temperature <i>Max</i>	°C	85.0000
Storage Temperature <i>Min</i>	°F	-40.0000
Storage Temperature <i>Max</i>	°F	85.0000
Storage Relative Humidity <i>Max</i>	%RH	95.0000
Mechanical Characteristics		
Connection to Network		By screw terminals: 4-25mm ²
Weight		0.263 kg
TECHNOLOGY		MOV+GSG
NETWORK CONFIGURATION		3 poles, 2W+G
CONNECTION METHOD		SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG
MOUNTING		Din Rail
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts
DIMENSIONS		See diagram
Standards		
Certification		UL Recognized
UL STANDARD		UL1449 5th Edition
UL FILE NUMBER		E326289
Part number		
480161		