



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x 8/20us)
- 5kA I_{mp} (2x 10/350us)
- 5kA I_n (10x 8/20us)
- Modular
- 2W+SHIELD+G

	Electrical Characteristics																																																							
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube L: Inductor D: Clamping diode</p>	<table border="1"> <tr><td>Max. DC operating voltage</td><td>U_c</td><td>53 Vdc</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>I_L</td><td>2.4 A</td></tr> <tr><td>Impulse current 2 x 10/350µs Test - D1 Category</td><td>I_{imp}</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td><td>I_n L/PE</td><td>5 kA</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL497B LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>48</td></tr> <tr><td>WIRES</td><td></td><td>2W+SHIELD+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>2.4</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-50</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>70</td></tr> <tr><td>MCOV</td><td>(V)</td><td>28</td></tr> <tr><td>I_n 10 impulses 8/20µs</td><td>(kA)</td><td>5</td></tr> <tr><td>I_{MAX} 8/20µs</td><td>(kA)</td><td>20</td></tr> <tr><td>I_{imp} 10/350µs</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>< 1</td></tr> </table>		Max. DC operating voltage	U _c	53 Vdc	Insertion loss		< 1 dB	Max. load current @25°C	I _L	2.4 A	Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I _n L/PE	5 kA	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	48	WIRES		2W+SHIELD+G	LINE CURRENT MAX	(A)	2.4	AMBIENT MIN	(C)	-50	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	70	MCOV	(V)	28	I _n 10 impulses 8/20µs	(kA)	5	I _{MAX} 8/20µs	(kA)	20	I _{imp} 10/350µs	(kA)	5	DATA SPEED	(Mbps)	10/100	INSERTION LOSS (@ FREQ)	(db)	< 1
Max. DC operating voltage	U _c	53 Vdc																																																						
Insertion loss		< 1 dB																																																						
Max. load current @25°C	I _L	2.4 A																																																						
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA																																																						
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I _n L/PE	5 kA																																																						
DATA SPD TYPE		UL497B LISTED																																																						
VOLTS	(V)	48																																																						
WIRES		2W+SHIELD+G																																																						
LINE CURRENT MAX	(A)	2.4																																																						
AMBIENT MIN	(C)	-50																																																						
AMBIENT MAX	(C)	+85																																																						
RESIDUAL VOLTAGE	(V)	70																																																						
MCOV	(V)	28																																																						
I _n 10 impulses 8/20µs	(kA)	5																																																						
I _{MAX} 8/20µs	(kA)	20																																																						
I _{imp} 10/350µs	(kA)	5																																																						
DATA SPEED	(Mbps)	10/100																																																						
INSERTION LOSS (@ FREQ)	(db)	< 1																																																						
Mechanical Characteristics																																																								
	<table border="1"> <tr><td>Connection to Network</td><td>By screw terminal: cross section 0.4-1.5mm²</td></tr> <tr><td>TECHNOLOGY</td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td>1 pair</td></tr> <tr><td>CONNECTION METHOD</td><td>Screw Terminal</td></tr> <tr><td>MOUNTING</td><td>DIN RAIL</td></tr> <tr><td>MATERIAL</td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td>DLAHM-48D3</td></tr> </table>	Connection to Network	By screw terminal: cross section 0.4-1.5mm ²	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 pair	CONNECTION METHOD	Screw Terminal	MOUNTING	DIN RAIL	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAHM-48D3																																			
Connection to Network	By screw terminal: cross section 0.4-1.5mm ²																																																							
TECHNOLOGY	SAD-GDT																																																							
NETWORK CONFIGURATION	1 pair																																																							
CONNECTION METHOD	Screw Terminal																																																							
MOUNTING	DIN RAIL																																																							
MATERIAL	Thermoplastic UL94-V0																																																							
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																																							
DIMENSIONS	See diagram																																																							
WEIGHT	0.30 lbs																																																							
SPARE PART	DLAHM-48D3																																																							
Standards																																																								
	<table border="1"> <tr><td>UL STANDARD</td><td>UL497B</td></tr> <tr><td>UL CATEGORY</td><td>QVGQ</td></tr> <tr><td>UL FILE NUMBER</td><td>E184939</td></tr> <tr><td>STANDARDS</td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td>ROHS</td></tr> </table>		UL STANDARD	UL497B	UL CATEGORY	QVGQ	UL FILE NUMBER	E184939	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																																												
UL STANDARD	UL497B																																																							
UL CATEGORY	QVGQ																																																							
UL FILE NUMBER	E184939																																																							
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																							
ENVIRONMENTAL STANDARDS	ROHS																																																							
Part number																																																								
641004																																																								

