



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I<sub>max</sub> (1x-8/20us)
- ↳ 5kA I<sub>mp</sub> (2x-10/350us)
- ↳ 5kA I<sub>n</sub> (10x-8/20us)
- ↳ Modular
- ↳ 2W+SHIELD+G



	<b>Electrical Characteristics</b>																																																													
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>170 Vdc</td></tr> <tr><td>Insertion loss</td><td></td><td>&lt; 1 dB</td></tr> <tr><td>Impulse current 2 x 10/350µs Test - D1 Category</td><td>I<sub>imp</sub></td><td>5 kA</td></tr> <tr><td>Nominal discharge current C2 Category</td><td>I<sub>n</sub></td><td>5 kA</td></tr> <tr><td>Max. Load current</td><td>IL</td><td>300 mA</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL497B LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>150</td></tr> <tr><td>WIRES</td><td></td><td>2W+Shield+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-40</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>210</td></tr> <tr><td>MCOV</td><td>(V)</td><td>170</td></tr> <tr><td>I<sub>N</sub> 10 impulses 8/20µs</td><td>(kA)</td><td>5</td></tr> <tr><td>I<sub>MAX</sub> 8/20µs</td><td>(kA)</td><td>20</td></tr> <tr><td>I<sub>imp</sub> 10/350µs</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>FREQUENCY</td><td>(MHz)</td><td>up to 10</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>&lt; 1</td></tr> <tr><td>CAPACITANCE</td><td>(pF)</td><td>&lt; 50</td></tr> </table>		Max. DC operating voltage	Uc	170 Vdc	Insertion loss		< 1 dB	Impulse current 2 x 10/350µs Test - D1 Category	I <sub>imp</sub>	5 kA	Nominal discharge current C2 Category	I <sub>n</sub>	5 kA	Max. Load current	IL	300 mA	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	150	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	210	MCOV	(V)	170	I <sub>N</sub> 10 impulses 8/20µs	(kA)	5	I <sub>MAX</sub> 8/20µs	(kA)	20	I <sub>imp</sub> 10/350µs	(kA)	5	DATA SPEED	(Mbps)	10/100	FREQUENCY	(MHz)	up to 10	INSERTION LOSS (@ FREQ)	(db)	< 1	CAPACITANCE	(pF)	< 50
Max. DC operating voltage	Uc	170 Vdc																																																												
Insertion loss		< 1 dB																																																												
Impulse current 2 x 10/350µs Test - D1 Category	I <sub>imp</sub>	5 kA																																																												
Nominal discharge current C2 Category	I <sub>n</sub>	5 kA																																																												
Max. Load current	IL	300 mA																																																												
DATA SPD TYPE		UL497B LISTED																																																												
VOLTS	(V)	150																																																												
WIRES		2W+Shield+G																																																												
LINE CURRENT MAX	(A)	0.3																																																												
AMBIENT MIN	(C)	-40																																																												
AMBIENT MAX	(C)	+85																																																												
RESIDUAL VOLTAGE	(V)	210																																																												
MCOV	(V)	170																																																												
I <sub>N</sub> 10 impulses 8/20µs	(kA)	5																																																												
I <sub>MAX</sub> 8/20µs	(kA)	20																																																												
I <sub>imp</sub> 10/350µs	(kA)	5																																																												
DATA SPEED	(Mbps)	10/100																																																												
FREQUENCY	(MHz)	up to 10																																																												
INSERTION LOSS (@ FREQ)	(db)	< 1																																																												
CAPACITANCE	(pF)	< 50																																																												
	<b>Mechanical Characteristics</b>																																																													
	<table border="1"> <tr><td>Connection to Network</td><td>By screw terminal: cross section 0.5-2.5mm<sup>2</sup></td></tr> <tr><td>TECHNOLOGY</td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td>1 Channel (2W+SHIELD+G)</td></tr> <tr><td>CONNECTION METHOD</td><td>Screw terminal</td></tr> <tr><td>MOUNTING</td><td>Din rail</td></tr> <tr><td>MATERIAL</td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td>DLAM-170D3</td></tr> </table>	Connection to Network	By screw terminal: cross section 0.5-2.5mm <sup>2</sup>	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)	CONNECTION METHOD	Screw terminal	MOUNTING	Din rail	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAM-170D3																																									
Connection to Network	By screw terminal: cross section 0.5-2.5mm <sup>2</sup>																																																													
TECHNOLOGY	SAD-GDT																																																													
NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)																																																													
CONNECTION METHOD	Screw terminal																																																													
MOUNTING	Din rail																																																													
MATERIAL	Thermoplastic UL94-V0																																																													
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																																													
DIMENSIONS	See diagram																																																													
WEIGHT	0.30 lbs																																																													
SPARE PART	DLAM-170D3																																																													
	<b>Standards</b>																																																													
	<table border="1"> <tr><td>Certification</td><td>UL Listed</td></tr> <tr><td>UL STANDARD</td><td>UL497B</td></tr> <tr><td>UL CATEGORY</td><td>QVQG</td></tr> <tr><td>UL FILE NUMBER</td><td>E184939</td></tr> <tr><td>STANDARDS</td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td>ROHS</td></tr> </table>	Certification	UL Listed	UL STANDARD	UL497B	UL CATEGORY	QVQG	UL FILE NUMBER	E184939	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																																																	
Certification	UL Listed																																																													
UL STANDARD	UL497B																																																													
UL CATEGORY	QVQG																																																													
UL FILE NUMBER	E184939																																																													
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																													
ENVIRONMENTAL STANDARDS	ROHS																																																													
	<b>Part number</b>																																																													
	<b>6406011</b>																																																													

