




- ↳ Hybrid MOV-GSG Technology
- ↳ UL1449 Type 1 LISTED
- ↳ 50kA Surge Current Rating per mode
- ↳ Extended life with no leakage current
- ↳ Visual LED fault indicator and audible alarm
- ↳ NEMA 6 (exceeds NEMA 4X or 4)
- ↳ Optional Type 2 LISTED with UL1283 Filter
- ↳ 10-Year warranty



| Características eléctricas | | |
|-----------------------------|------|---|
| POWER SPD TYPE | | UL1449 TYPE 2 LISTED |
| TENSION | (V) | 600 |
| AC/DC/DC PV/RF | | AC |
| FASE | (PH) | 3D |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -35 |
| AMBIENT MAX | (C) | +80 |
| MODOS | | L-L, L-G |
| VPR | (V) | 3000/-/1800/- |
| MCOV | (V) | 690/690/-/- |
| IN | (kA) | 20 |
| Icc cortocircuito | (kA) | 200 |
| IMAX | (kA) | 50 |
| Instalación | | |
| Operating Temperature | °C | -40.0000 |
| Operating Temperature | °C | 85.0000 |
| Operating Temperature | °F | -40.0000 |
| Operating Temperature | °F | 85.0000 |
| Operating Relative Humidity | %RH | Can be submerged |
| Operating Altitude | Ft | 2000.0000 |
| Operating Altitude | Ft | 6500.0000 |
| Housing/Enclosure material | | Aluminum cast |
| Mounting | | Side mount |
| IP Environmental rating | | IP66 |
| NEMA Environmental rating | | NEMA 6 |
| Installation Location | | Indoor / outdoor |
| Accesorio | | Soportes |
| Product Dimension | mm | 102.0000 |
| Product Dimension | mm | 62.0000 |
| Product Dimension | mm | 88.0000 |
| Product Dimension | In | 4.0160 |
| Product Dimension | In | 2.4410 |
| Product Dimension | In | 3.4650 |
| Miscelánea | | |
| Individual Pack | | Yes |
| Storage Temperature | °C | -40.0000 |
| Storage Temperature | °C | 85.0000 |
| Storage Temperature | °F | -40.0000 |
| Storage Temperature | °F | 85.0000 |
| Características mecánicas | | |
| TECNOLOGIA | | MOV-GSG |
| CONFIGURACION DE RED | | 3PH, 3W+G, Delta |
| FORMA DE CONEXION | | 36" #12 AWG LEADS |
| MONTAJE | | SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER) |
| MATERIAL | | Aluminum cast |
| NEMA RATING (IP RATING) | | 6 |
| DESCONEXION SEGURA | | Yes, no upstream over current protection required |
| REAL-TIME DIAGNOSTICS | | LED and audible alarm |
| DIMENSIONS | | See diagram |
| WEIGHT | | 2.5 lbs. |
| Normas | | |
| UL STANDARD | | UL1449 5th Edition |
| UL CATEGORY | | VZCA, VZCA7 |
| UL FILE NUMBER | | E326289 |
| NORMAS | | NOM-003-SCFI-2014, NOM-001-SCFI-1993 |
| ENVIRONMENTAL STANDARDS | | ROHS |

| |
|--------|
| Código |
| 750814 |

