



- 1 Pair Protection
- Modes of Protection L-L,L-G
- Conduit Mounting-1/2 inch NPT
- Direct Transducer Mount
- Parallel or Series Connection Options

| Electrical Characteristics | | |
|--------------------------------------|------|---------------------------------------|
| VOLTS | (V) | 48 |
| MAXIMUM LINE VOLTAGE | (V) | 54 |
| WIRES | | 4W+GROUND |
| LINE CURRENT MAX | (A) | 0.3 |
| AMBIENT MIN | (C) | -55 |
| AMBIENT MAX | (C) | +85 |
| PROTECTION LEVEL | (V) | 82 |
| IN 15 impulses 8/20µs | (kA) | 10 |
| IMAX 8/20µs | (kA) | 15 |
| Installation | | |
| Operating Relative Humidity $_{Max}$ | %RH | Can be submerged |
| Operating Altitude $_{Min}$ | Ft | 2000.0000 |
| Operating Altitude $_{Max}$ | Ft | 6500.0000 |
| Housing/Enclosure material | | Stainless Steel |
| Mounting | | Conduit-1/2" NPT |
| Installation Location | | Indoor / outdoor |
| Product Dimension L | mm | 114.3000 |
| Product Dimension H | mm | 26.0000 |
| Product Dimension W | mm | 27.9400 |
| Product Dimension L | In | 4.5000 |
| Product Dimension H | In | 1.0000 |
| Product Dimension W | In | 1.1000 |
| Product Weight | lbs | 0.8000 |
| Miscellaneous | | |
| Individual Pack | | Yes |
| Mechanical Characteristics | | |
| CONNECTION METHOD | | Parallel- #16 AWG Copper Wires-Tinned |
| Part number | | |
| 6338 | | |