



M50-230S-A



- Hybrid MOV-GSG Technology
- UL1449 Type 1 LISTED
- 50kA Surge Current Rating per mode
- Extended life with no leakage current
- Visual LED fault indicator and audible alarm
- NEMA 6 (exceeds NEMA 4X or 4)
- Optional Type 2 LISTED with UL1283 Filter
- 10-Year warranty

	Electrical Characteristics																																														
	<table border="1"> <tr> <td>POWER SPD TYPE</td> <td></td> <td>UL1449 TYPE 1 LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V)</td> <td>230</td> </tr> <tr> <td>AC/DC/DC PV/RF</td> <td></td> <td>AC</td> </tr> <tr> <td>PHASE</td> <td>(PH)</td> <td>1</td> </tr> <tr> <td>AMPS</td> <td>(A)</td> <td>N/A</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-35</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+80</td> </tr> <tr> <td>MODES</td> <td></td> <td>L-L, L-G, L-N</td> </tr> <tr> <td>VPR</td> <td>(V)</td> <td>1200/1500/1200</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>280/280/240</td> </tr> <tr> <td>IN</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>15 impulses 8/20μs</td> <td></td> <td></td> </tr> <tr> <td>SCCR</td> <td>(kA)</td> <td>150</td> </tr> <tr> <td>IMAX</td> <td>(kA)</td> <td>50</td> </tr> <tr> <td>8/20μs</td> <td></td> <td></td> </tr> </table>		POWER SPD TYPE		UL1449 TYPE 1 LISTED	VOLTS	(V)	230	AC/DC/DC PV/RF		AC	PHASE	(PH)	1	AMPS	(A)	N/A	AMBIENT MIN	(C)	-35	AMBIENT MAX	(C)	+80	MODES		L-L, L-G, L-N	VPR	(V)	1200/1500/1200	MCOV	(V)	280/280/240	IN	(kA)	20	15 impulses 8/20μs			SCCR	(kA)	150	IMAX	(kA)	50	8/20μs		
POWER SPD TYPE		UL1449 TYPE 1 LISTED																																													
VOLTS	(V)	230																																													
AC/DC/DC PV/RF		AC																																													
PHASE	(PH)	1																																													
AMPS	(A)	N/A																																													
AMBIENT MIN	(C)	-35																																													
AMBIENT MAX	(C)	+80																																													
MODES		L-L, L-G, L-N																																													
VPR	(V)	1200/1500/1200																																													
MCOV	(V)	280/280/240																																													
IN	(kA)	20																																													
15 impulses 8/20μs																																															
SCCR	(kA)	150																																													
IMAX	(kA)	50																																													
8/20μs																																															
Mechanical Characteristics																																															
<table border="1"> <tr> <td>Weight</td> <td>1 kg</td> </tr> <tr> <td>TECHNOLOGY</td> <td>MOV-GSG</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td>1PH, 2W+G, Single</td> </tr> <tr> <td>CONNECTION METHOD</td> <td>36" #12 AWG LEADS</td> </tr> <tr> <td>MOUNTING</td> <td>SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER)</td> </tr> <tr> <td>MATERIAL</td> <td>Aluminum cast</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td>6 (IP66)</td> </tr> <tr> <td>FAIL-SAFE BEHAVIOR</td> <td>Yes, no upstream over current protection required</td> </tr> <tr> <td>REAL-TIME DIAGNOSTICS</td> <td>LED and audible alarm</td> </tr> <tr> <td>DIMENSIONS</td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td>2.5 lbs.</td> </tr> </table>		Weight	1 kg	TECHNOLOGY	MOV-GSG	NETWORK CONFIGURATION	1PH, 2W+G, Single	CONNECTION METHOD	36" #12 AWG LEADS	MOUNTING	SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER)	MATERIAL	Aluminum cast	NEMA RATING (IP RATING)	6 (IP66)	FAIL-SAFE BEHAVIOR	Yes, no upstream over current protection required	REAL-TIME DIAGNOSTICS	LED and audible alarm	DIMENSIONS	See diagram	WEIGHT	2.5 lbs.																								
Weight	1 kg																																														
TECHNOLOGY	MOV-GSG																																														
NETWORK CONFIGURATION	1PH, 2W+G, Single																																														
CONNECTION METHOD	36" #12 AWG LEADS																																														
MOUNTING	SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER)																																														
MATERIAL	Aluminum cast																																														
NEMA RATING (IP RATING)	6 (IP66)																																														
FAIL-SAFE BEHAVIOR	Yes, no upstream over current protection required																																														
REAL-TIME DIAGNOSTICS	LED and audible alarm																																														
DIMENSIONS	See diagram																																														
WEIGHT	2.5 lbs.																																														
Standards																																															
<table border="1"> <tr> <td>UL STANDARD</td> <td>UL1449 5th Edition</td> </tr> <tr> <td>UL CATEGORY</td> <td>VZCA</td> </tr> <tr> <td>UL FILE NUMBER</td> <td>E326289</td> </tr> <tr> <td>STANDARDS</td> <td>NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td>ROHS</td> </tr> </table>		UL STANDARD	UL1449 5th Edition	UL CATEGORY	VZCA	UL FILE NUMBER	E326289	STANDARDS	NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																																				
UL STANDARD	UL1449 5th Edition																																														
UL CATEGORY	VZCA																																														
UL FILE NUMBER	E326289																																														
STANDARDS	NOM-003-SCFI-2014, NOM-001-SCFI-1993																																														
ENVIRONMENTAL STANDARDS	ROHS																																														
Part number																																															
751303																																															