





- Hybrid MOV-GSG Technology
- 50kA Surge Current Rating per mode
- Extended life with no leakage current
- Visual LED fault indicator and audible alarm
- NEMA 6 (exceeds NEMA 4X or 4)
- 10-Year warranty

	Electrical Characteristics	
	POWER SPD TYPE	-
	VOLTS	(V) 347/600
	AC/DC/DC PV/RF	AC
	PHASE	(PH) 3Y
	AMPS	(A) N/A
	AMBIENT MIN	(C) -35
	AMBIENT MAX	(C) +80
	MODES	L-L, L-N, L-G, N-G
	VPR	(V) 3000/1500/1800/1800
	MCOV	(V) 690/400/400/350
	IN	(kA) 20
	15 impulses 8/20μs	(kA) 150
	SCCR	(kA) 150
	Mechanical Characteristics	
	TECHNOLOGY	MOV-GSG
	NETWORK CONFIGURATION	3PH, 4W+G, Wye
	CONNECTION METHOD	36" #12 AWG LEADS
	MOUNTING	SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER)
	MATERIAL	Aluminum cast
	NEMA RATING (IP RATING)	6 (IP66)
	FAIL-SAFE BEHAVIOR	Yes, no upstream over current protection required
	REAL-TIME DIAGNOSTICS	LED and audible alarm
	DIMENSIONS	See diagram
	WEIGHT	2.5 lbs.
	Standards	
	STANDARDS	NOM-003-SCFI-2014, NOM-001-SCFI-1993
	ENVIRONMENTAL STANDARDS	ROHS
	Part number	
	751601	