





UL TYPE 1 SPD - I_{max} 75kA - I_n 20/30kA - Modular Assembly

CITEL

DS74US-240Y/G



- ↳ Hybrid Technology (Multi-MOV+GSG)
- ↳ UL1449 Type 1 LISTED
- ↳ 75kA Surge Current Rating per module
- ↳ Visual fault indicator and remote contacts
- ↳ 10-Year warranty



V : Varistor de alta energía
 Ft : Fusible térmico
 C : Contacto de teleseñalización
 t* : Sistema de desconexión térmica
 MI : Indicador de desconexión

Características eléctricas

| | | |
|-------------------------------|------|----------------------|
| POWER SPD TYPE | | UL1449 TYPE 1 LISTED |
| TENSION | (V) | 120/208/240 |
| AC/DC/DC PV/RF | | AC |
| FASE | (PH) | 3Y |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -40 |
| AMBIENT MAX | (C) | +85 |
| MODOS | | L-L, L-N, L-G, N-G |
| VPR | (V) | 1800/1000/1200/1200 |
| MCOV | (V) | 320/320/255 |
| IN | (kA) | 20 |
| I _{cc} cortocircuito | (kA) | 200 |
| IMAX | (kA) | 75 |
| RELATIVE HUMIDITY | (%) | 95% |

Características mecánicas

| | | |
|-------------------------|--|--|
| Peso | | 0.513 kg |
| TECNOLOGIA | | Multi-MOV+GSG |
| CONFIGURACION DE RED | | 3PH, 4W+G, Wye |
| FORMA DE CONEXION | | SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG |
| MONTAJE | | Din Rail |
| MATERIAL | | Thermoplastic UL94-V0 |
| NEMA RATING (IP RATING) | | NEMA 2 (IP20) |
| DESCONEXION SEGURA | | Disconnection via fuse-link |
| REAL-TIME DIAGNOSTICS | | Visual indicator and remote contacts |
| DIMENSIONS | | See diagram |

Normas

| | | |
|-------------------------|--|--------------------------------------|
| UL STANDARD | | UL1449 5th Edition |
| UL CATEGORY | | VZCA, VZCA7 |
| UL FILE NUMBER | | E326289 |
| NORMAS | | NOM-003-SCFI-2014, NOM-001-SCFI-1993 |
| ENVIRONMENTAL STANDARDS | | ROHS |

Código

321934552

