




CITEL

UL TYPE 4CA - I_{max} 22kA - I_n 10kA

MLPC1-277L-V/50



- ↳ UL1449 Type 2 SPD
- ↳ 120 VAC to 277 VAC
- ↳ Plate Mounting
- ↳ Screw Terminal Connection
- ↳ Series or Parallel Installation
- ↳ Status indicator
- ↳ Disconnection AC end of life
- ↳ EN 61643-11 compliance
- ↳ Total Surge Rating – I_{total}: 20kA
- ↳ ANSI C136.2



V: Varistor
 GSG: Specific gas tube
 LED: Disconnection indicator
 Ft: Thermal fuse
 t*: Thermal system disconnection

Electrical Characteristics		
POWER SPD TYPE		UL1449 TYPE 2 LISTED
VOLTS	(V)	277
AC/DC/DC PV/RF		AC
PHASE	(PH)	1
AMPS	(A)	5
AMBIENT MIN	(C)	-40
AMBIENT MAX	(C)	+85
MODES		L-L, L-G, L-N, N-G
VPR	(V)	1500/1500/1200
MCOV	(V)	385/385/255
IN	(kA)	5
15 impulses 8/20µs		
SCCR	(kA)	18
IMAX	(kA)	10
8/20µs		
Mechanical Characteristics		
TECHNOLOGY		MOV-GSG
NETWORK CONFIGURATION		2 pole, 2W+G, Single/Spilt Phase
CONNECTION METHOD		Screw Terminal (4-10AWG)
MOUNTING		FLANGE MOUNT
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		LED Indicator
DIMENSIONS		See diagram
WEIGHT		0.30 lbs
Standards		
Certification		UL Listed / IMQ
UL STANDARD		UL1449 5th Edition
UL CATEGORY		VZCA2, VZCA8
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993
ANSI/IEEE C62.41		Category C 20kV/10kA
ANSI/IEEE C136.2		Enhanced Category 10kV/5kA
ENVIRONMENTAL STANDARDS		ROHS
Part number		
831322		

