

MDS750S-480D



- UL1449 5th edition
- All Mode Protection
- I_{total}- 750kA 8/20us
- I_{max}/phase-375kA 8/20us
- I_{imp}- 15kA 10/350us/phase
- UL Nominal Discharge Current (I_n) 20kA (All models)
- UL Short-circuit Current Rating (SCCR) 200kA (All models)
- UL96A Master Label Compliant
- Internal Surge Rated Fusing
- Enhanced Diagnostics - % of protection present, surge counter, audible, remote, test /mute
- Replaceable Modular Design for SPD and Filter (if applicable)
- Optional Listing as UL Type 2 with UL1283 Filter and cUL
- NEMA 4/12 (Stainless Steel NEMA 4X optional)
- 10-year Warranty

Electrical Characteristics		
POWER SPD TYPE		UL1449 TYPE 1 LISTED
VOLTS	(V)	480
AC/DC/DC PV/RF		AC
PHASE	(PH)	3D
AMPS	(A)	N/A
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+85
MODES		L-L, L-G
VPR	(V)	2000/2000
MCOV	(V)	550/550
I _N	(kA)	20
15 impulses 8/20μs		
SCCR	(kA)	200
I _{MAX}	(kA)	375
8/20μs		
Option		
Remote status dry contact electrical ratingMax Voltage	V	125.0000
Remote status dry contact electrical ratingMax Current	A	0.5000
RFI Filter		Yes
Installation		
Wiring type		Screw
Stranded Wire cross sectionMin	mm ²	5.0000
Wire gaugeMin	AWG	10.0000
Torque	Nm	4
Torque	in-lbs	35
Operating TemperatureMin	°C	-40.0000
Operating TemperatureMax	°C	85.0000
Operating TemperatureMin	°F	-40.0000
Operating TemperatureMax	°F	85.0000
Operating Relative HumidityMax	%RH	95
Operating AltitudeMin	Ft	2000.0000
Operating AltitudeMax	Ft	6500.0000
Housing/Enclosure material		Metal
Flammability ratingUL 94		V0
Mounting		WALL MOUNT
IP Environmental ratingIP		IP56
NEMA Environmental ratingNEMA		NEMA 4
Installation Location		Indoor / outdoor
Spare part		Module
Accessories		brackets
Product DimensionL	mm	360.6000
Product DimensionH	mm	406.4000
Product DimensionW	mm	159.8000
Product DimensionL	In	14.2000
Product DimensionH	In	16.0000
Product DimensionW	In	6.2900
Miscellaneous		

MDS750S-480D

Individual Pack		Yes
Storage Temperature _{Min}	°C	-40.0000
Storage Temperature _{Max}	°C	85.0000
Storage Temperature _{Min}	°F	-40.0000
Storage Temperature _{Max}	°F	85.0000
Mechanical Characteristics		
TECHNOLOGY		Multi-TMOV
NETWORK CONFIGURATION		3PH, 3W+G, Delta
CONNECTION METHOD		Screw Terminal (4-10AWG)
MOUNTING		FLANGE MOUNT
MATERIAL		Steel
NEMA RATING (IP RATING)		IP65
FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required
REAL-TIME DIAGNOSTICS		% of protection present LED, audible alarm and remote contacts. Optional surge counter.
DIMENSIONS		See diagram
WEIGHT		25 lbs
Standards		
UL STANDARD		UL1449 5th Edition, UL1283
UL CATEGORY		VZCA, VZCA7, FOKY, FOKY7
UL FILE NUMBER		E326289, E467909
ANSI/IEEE C62.41		Category C 20kV/10kA
ENVIRONMENTAL STANDARDS		ROHS
Part number		
890663		