




UL TYPE 1 SPD - I_{max} 40kA - I_n 20kA - Modular

CITEL

DS42S-400



- ↳ UL1449 TYPE 1 LISTED SPD
- ↳ MOV Technology
- ↳ 40kA Surge Current Rating
- ↳ Visual fault indicator and remote contacts
- ↳ 10-Year warranty



Características eléctricas	
Red	230 V monofásica
Modo(s) de protección	Modo común
POWER SPD TYPE	UL1449 TYPE 1 LISTED
TENSION (V)	480/277
AC/DC/DC PV/RF	AC
FASE (PH)	3Y
AMPS (A)	N/A
AMBIENT MIN (C)	-35
AMBIENT MAX (C)	+60
MODOS	L-L, L-G
VPR (V)	2500/-/1500/-
MCOV (V)	680/-/420/-
IN (kA)	20
I _{cc cortocircuito} (kA)	100
IMAX (kA)	40
I _{imp} (kA)	4
Características mecánicas	
IP degree	IP 20
Formato	Caja modular desenchufable
Modo de fallo	Desconexión de la red Baja Tensión
TECNOLOGIA	MOV
CONFIGURACION DE RED	2 pole, 2W+G, Single/Spilt Phase
FORMA DE CONEXION	SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG
MONTAJE	Din Rail
MATERIAL	Thermoplastic UL94-V0
NEMA RATING (IP RATING)	NEMA 2 (IP20)
DESCONEXION SEGURA	Disconnection via fuse-link
REAL-TIME DIAGNOSTICS	Visual indicator and remote contacts
DIMENSIONS	See diagram
WEIGHT	0.60 lbs
SPARE PART	DSM40-400
Normas	
Certificación	UL / CSA / TUV Süd
UL STANDARD	UL1449 5th Edition
UL CATEGORY	VZCA, VZCA7
UL FILE NUMBER	E326289
NORMAS	NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS	ROHS
Código	
461421	

