



## DLA2-06DBC



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I<sub>max</sub>
- 5kA I<sub>mp</sub>
- 5kA I<sub>n</sub>
- Modular
- 4W+SHIELD+G



	<b>Electrical Characteristics</b>																																																																
 <p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>MIC/T2, 10BaseT</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>U<sub>c</sub></td> <td>8 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>&gt; 20 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>I<sub>imp</sub></td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>I<sub>n</sub></td> <td>5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>4.7 Ohm</td> </tr> <tr> <td>DATA SPD TYPE</td> <td></td> <td>UL497B LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V)</td> <td>6</td> </tr> <tr> <td>WIRES</td> <td></td> <td>4W+SHIELD+GROUND</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A)</td> <td>0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-50</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V)</td> <td>20</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>8/72/72</td> </tr> <tr> <td>IMAX 8/20µs</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>I<sub>imp</sub> 10/350µs</td> <td>(kA)</td> <td>5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps)</td> <td>10/100/1000</td> </tr> <tr> <td>FREQUENCY</td> <td>(MHz)</td> <td>&gt;20</td> </tr> <tr> <td>INSERTION LOSS (@ FREQ)</td> <td>(db)</td> <td>&lt; 1</td> </tr> <tr> <td>CAPACITANCE</td> <td>(pF)</td> <td>&lt; 50</td> </tr> </table>		Network		MIC/T2, 10BaseT	Max. DC operating voltage	U <sub>c</sub>	8 Vdc	Max. frequency	f max.	> 20 MHz	Max. load current @25°C	IL	300 mA	Impulse current 2 x 10/350µs Test - D1 Category	I <sub>imp</sub>	5 kA	Nominal discharge current C2 Category	I <sub>n</sub>	5 kA	Line resistance (± 10%)		4.7 Ohm	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	6	WIRES		4W+SHIELD+GROUND	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-50	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	20	MCOV	(V)	8/72/72	IMAX 8/20µs	(kA)	20	I <sub>imp</sub> 10/350µs	(kA)	5	DATA SPEED	(Mbps)	10/100/1000	FREQUENCY	(MHz)	>20	INSERTION LOSS (@ FREQ)	(db)	< 1	CAPACITANCE	(pF)	< 50
Network		MIC/T2, 10BaseT																																																															
Max. DC operating voltage	U <sub>c</sub>	8 Vdc																																																															
Max. frequency	f max.	> 20 MHz																																																															
Max. load current @25°C	IL	300 mA																																																															
Impulse current 2 x 10/350µs Test - D1 Category	I <sub>imp</sub>	5 kA																																																															
Nominal discharge current C2 Category	I <sub>n</sub>	5 kA																																																															
Line resistance (± 10%)		4.7 Ohm																																																															
DATA SPD TYPE		UL497B LISTED																																																															
VOLTS	(V)	6																																																															
WIRES		4W+SHIELD+GROUND																																																															
LINE CURRENT MAX	(A)	0.3																																																															
AMBIENT MIN	(C)	-50																																																															
AMBIENT MAX	(C)	+85																																																															
RESIDUAL VOLTAGE	(V)	20																																																															
MCOV	(V)	8/72/72																																																															
IMAX 8/20µs	(kA)	20																																																															
I <sub>imp</sub> 10/350µs	(kA)	5																																																															
DATA SPEED	(Mbps)	10/100/1000																																																															
FREQUENCY	(MHz)	>20																																																															
INSERTION LOSS (@ FREQ)	(db)	< 1																																																															
CAPACITANCE	(pF)	< 50																																																															
	<b>Mechanical Characteristics</b>																																																																
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.5-2.5mm<sup>2</sup></td> </tr> <tr> <td>Format</td> <td></td> <td>Plug-in DIN box</td> </tr> <tr> <td>Operating and storage temperature</td> <td></td> <td>-40/+85°C</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>TECHNOLOGY</td> <td></td> <td>SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td></td> <td>2 Channels (4W+G)</td> </tr> <tr> <td>CONNECTION METHOD</td> <td></td> <td>Screw Terminal</td> </tr> <tr> <td>MOUNTING</td> <td></td> <td>Din Rail</td> </tr> <tr> <td>MATERIAL</td> <td></td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td></td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td></td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td></td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td></td> <td>DLA2M-06DBC</td> </tr> </table>		Technology		GDT+Clamping diode	Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>	Format		Plug-in DIN box	Operating and storage temperature		-40/+85°C	Failsafe mode		Short-circuit	TECHNOLOGY		SAD-GDT	NETWORK CONFIGURATION		2 Channels (4W+G)	CONNECTION METHOD		Screw Terminal	MOUNTING		Din Rail	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram	WEIGHT		0.30 lbs	SPARE PART		DLA2M-06DBC																					
Technology		GDT+Clamping diode																																																															
Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>																																																															
Format		Plug-in DIN box																																																															
Operating and storage temperature		-40/+85°C																																																															
Failsafe mode		Short-circuit																																																															
TECHNOLOGY		SAD-GDT																																																															
NETWORK CONFIGURATION		2 Channels (4W+G)																																																															
CONNECTION METHOD		Screw Terminal																																																															
MOUNTING		Din Rail																																																															
MATERIAL		Thermoplastic UL94-V0																																																															
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																																															
DIMENSIONS		See diagram																																																															
WEIGHT		0.30 lbs																																																															
SPARE PART		DLA2M-06DBC																																																															
	<b>Standards</b>																																																																
	<table border="1"> <tr> <td>Certification</td> <td></td> <td>UL Listed</td> </tr> <tr> <td>UL STANDARD</td> <td></td> <td>UL497B</td> </tr> <tr> <td>UL CATEGORY</td> <td></td> <td>QVGQ</td> </tr> <tr> <td>UL FILE NUMBER</td> <td></td> <td>E184939</td> </tr> <tr> <td>STANDARDS</td> <td></td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td></td> <td>ROHS</td> </tr> </table>		Certification		UL Listed	UL STANDARD		UL497B	UL CATEGORY		QVGQ	UL FILE NUMBER		E184939	STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS																																													
Certification		UL Listed																																																															
UL STANDARD		UL497B																																																															
UL CATEGORY		QVGQ																																																															
UL FILE NUMBER		E184939																																																															
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																															
ENVIRONMENTAL STANDARDS		ROHS																																																															
	<b>Part number</b>																																																																
	640131																																																																