



- UL1449 LISTED SPD-Type 4CA
- MOV Technology
- 40kA Surge Current Rating
- Visual fault indicator and remote contacts
- 10-Year warranty



Electrical Characteristics

| | | |
|--------------------------|------|-------------------------|
| POWER SPD TYPE | | UL1449 5th Ed. TYPE 4CA |
| VOLTS | (V) | 1000 |
| AC/DC/DC PV/RF | | AC |
| PHASE | (PH) | 1 |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -40 |
| AMBIENT MAX | (C) | +60 |
| MODES | | L-G |
| MLV | (V) | 6660 |
| MCOV | (V) | 1000 |
| IN | (kA) | 20 |
| 15 impulses 8/20 μ s | | |
| IMAX | (kA) | 40 |
| 8/20 μ s | | |

Mechanical Characteristics


| | |
|-------------------------|--|
| Technology | MOV |
| Weight | 0.125 kg |
| CONNECTION METHOD | SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG |
| MOUNTING | Din Rail |
| MATERIAL | Thermoplastic UL94-V0 |
| NEMA RATING (IP RATING) | NEMA 2 (IP20) |
| FAIL-SAFE BEHAVIOR | Disconnection via fuse-link |
| REAL-TIME DIAGNOSTICS | Visual indicator and remote contacts |
| DIMENSIONS | See diagram |

Standards

| | |
|-------------------------|--|
| Certification | UL Recognized |
| UL STANDARD | UL1449 5th Edition |
| UL CATEGORY | VZCA2, VZCA8 |
| UL FILE NUMBER | E326289 |
| STANDARDS | IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993 |
| ENVIRONMENTAL STANDARDS | ROHS |

Part number

462921



V: High-energy varistor
 Ft: Thermal fuse
 C: Remote signal contact
 t°: Thermal disconnection system
 MI: Disconnection indicator

