




- 1 Pair Protection
- Modes of Protection L-L,L-G
- Conduit Mounting-1/2 inch NPT
- Direct Transducer Mount
- Parallel or Series Connection Options



Electrical Characteristics		
VOLTS	(V)	24
MAXIMUM LINE VOLTAGE	(V)	32
WIRES		4W+GROUND
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-55
AMBIENT MAX	(C)	+85
PROTECTION LEVEL	(V)	38
IN	(kA)	10
		15 impulses 8/20µs
IMAX	(kA)	15
		8/20µs
Installation		
Operating Relative Humidity $_{Max}$	%RH	Can be submerged
Operating Altitude $_{Min}$	Ft	2000.0000
Operating Altitude $_{Max}$	Ft	6500.0000
Housing/Enclosure material		Stainless Steel
Mounting		Conduit-1/2" NPT
Installation Location		Indoor / outdoor
Product Dimension L	mm	114.3000
Product Dimension H	mm	26.0000
Product Dimension W	mm	27.9400
Product Dimension L	In	4.5000
Product Dimension H	In	1.0000
Product Dimension W	In	1.1000
Product Weight	lbs	0.8000
Miscellaneous		
Individual Pack		Yes
Mechanical Characteristics		
CONNECTION METHOD		Parallel- #16 AWG Copper Wires-Tinned
Part number		
6336		