



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I<sub>max</sub> (1x 8/20us)
- ↳ 5kA I<sub>mp</sub> (2x 10/350us)
- ↳ 5kA I<sub>n</sub> (10x 8/20us)
- ↳ Modular with Fault Indicator
- ↳ 2W+SHIELD+G
- ↳ Common/Differential Mode Protection

Características eléctricas		
Tensión DC máx. de operación	Uc	28 Vdc
Corriente de descarga nominal X-C (Línea/Tierra) <i>Prueba 8/20µs x 10 - categoría C2</i>	In L/PE	5 kA
DATA SPD TYPE		UL497B LISTED
TENSION	(V)	24
WIRES		RJ11 Connector
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-50
AMBIENT MAX	(C)	+85
RESIDUAL VOLTAGE	(V)	40
MCOV	(V)	28/
IMAX	(kA)	20
I <sub>imp</sub>	(kA)	5
DATA SPEED	(Mbps)	up to 10MHz
INSERTION LOSS (@ FREQ)	(db)	< 1
CAPACITANCE	(pF)	< 50
Características mecánicas		
Conexión a la red		Por terminales de tornillos : 0.5-2.5 mm <sup>2</sup>
TECNOLOGIA		SAD-GDT
CONFIGURACION DE RED		1 pair
FORMA DE CONEXION		RJ11 Connector
MONTAJE		Wall mount
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
DIMENSIONS		See diagram
WEIGHT		0.30 lbs
SPARE PART		DLASM-24D3
Normas		
UL STANDARD		UL497B
UL CATEGORY		QVGQ
UL FILE NUMBER		E184939
NORMAS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Código		
641303		

