



- Quarter wave coaxial protector type N
- Frequency : 870-960 MHz
- Low insertion loss
- $I_{max} > 50 \text{ kA}$
- Maintenance free
- Bi-directional
- IP65



Electrical Characteristics		
Frequency range	f	870-960 MHz
Insertion loss		< 0.2 dB
Return loss		> 20 dB
Impedance		50 ohms
VSWR		<1.2:1
Max. load current @25°C	IL	10 A
Protection mode(s)		Common mode
Impulse current 2 x 10/350µs Test - D1 Category	limp	25 kA
Nominal discharge current C2 Category	In	25 kA
Max Power @f mini.		356 W
DC Pass		No
RF Power Maximum	W	1500.0000
Return Loss Minimum	db	>20
VSWR Maximum	:1	<1.2:1
Max Total Discharge Current $I_{max} (8/20\mu s \times 1)$	kA	40.0000
Max Discharge Current $I_{max} (8/20\mu s \times 1)$	kA	40.0000
Installation		
Operating Temperature $_{Min}$	°C	-45.0000
Operating Temperature $_{Max}$	°C	85.0000
Operating Temperature $_{Min}$	°F	-50.0000
Operating Temperature $_{Max}$	°F	85.0000
Operating Relative Humidity $_{Max}$	%RH	Can be submerged
Operating Altitude $_{Min}$	Ft	2000.0000
Operating Altitude $_{Max}$	Ft	6500.0000
Housing/Enclosure material		Cu, Zn, Sn plated Brass
Mounting		Bracket or through hole
IP Environmental rating $_{IP}$		IP65
NEMA Environmental rating $_{NEMA}$		NEMA 4
Installation Location		Indoor / outdoor
Accessories		BK
Product Dimension $_{L}$	mm	76.0000
Product Dimension $_{L}$	In	2.9920
Miscellaneous		
Individual Pack		No
Storage Temperature $_{Min}$	°C	-40.0000
Storage Temperature $_{Max}$	°C	85.0000
Storage Temperature $_{Min}$	°F	-40.0000
Storage Temperature $_{Max}$	°F	85.0000
Mechanical Characteristics		
Connection to Network		Connector TNC Female/Female
Contacts		Bronze/Surface Au-Ag
Insulation material		PTFE
Standards		
RohS compliance		Yes
Part number		
621126		