



# CITEL

## DS50PV-600



?



| Características eléctricas                        |                 |                                                 |
|---------------------------------------------------|-----------------|-------------------------------------------------|
| Modo(s) de protección                             |                 | Modo común                                      |
| Nivel de protección +/-PE (-/PE)<br>@ In (8/20µs) | Up              | 2.5 kV                                          |
| Maximum Discharge Current                         | kA              | 40.0000                                         |
| Maximum Discharge Current                         | kA              | 40.0000                                         |
| Maximum Discharge Current                         | kA              | 40.0000                                         |
| Voltage Protection Level                          | V               | 4000.0000                                       |
| Opción                                            |                 |                                                 |
| RFI Filter                                        |                 | no                                              |
| Instalación                                       |                 |                                                 |
| Wiring type                                       |                 | Screw                                           |
| Solid wire cross section                          | mm <sup>2</sup> | 2.5000                                          |
| Solid Wire cross section                          | mm <sup>2</sup> | 35.0000                                         |
| Stranded Wire cross section                       | mm <sup>2</sup> | 2.5000                                          |
| Stranded wire cross section                       | mm <sup>2</sup> | 25.0000                                         |
| Wire gauge                                        | AWG             | 13.0000                                         |
| Wire gauge                                        | AWG             | 4.0000                                          |
| Torque                                            | Nm              | 2.0 - 2.5                                       |
| Torque                                            | in-lbs          | 17.8 - 22.1                                     |
| Strip Length                                      | mm              | 13.0000                                         |
| Strip Length                                      | in              | 0.5000                                          |
| Operating Temperature                             | °C              | -40.0000                                        |
| Operating Temperature                             | °C              | 85.0000                                         |
| Operating Temperature                             | °F              | -40.0000                                        |
| Operating Temperature                             | °F              | 85.0000                                         |
| Operating Relative Humidity                       | %RH             | 95                                              |
| Operating Altitude                                | Ft              | 2000.0000                                       |
| Operating Altitude                                | Ft              | 6500.0000                                       |
| Housing/Enclosure material                        |                 | Thermoplastic                                   |
| Flammability rating                               |                 | V0                                              |
| Mounting                                          |                 | Din Rail                                        |
| IP Environmental rating                           |                 | IP20                                            |
| NEMA Environmental rating                         |                 | NEMA 1                                          |
| Installation Location                             |                 | Indoor                                          |
| Spare part                                        |                 | Module                                          |
| Product Dimension                                 | mm              | 99.0000                                         |
| Product Dimension                                 | mm              | 67.0000                                         |
| Product Dimension                                 | mm              | 36.0000                                         |
| Product Dimension                                 | In              | 3.8900                                          |
| Product Dimension                                 | In              | 2.6400                                          |
| Product Dimension                                 | In              | 1.4200                                          |
| Miscelánea                                        |                 |                                                 |
| Individual Pack                                   |                 | Yes                                             |
| Storage Temperature                               | °C              | -40.0000                                        |
| Storage Temperature                               | °C              | 85.0000                                         |
| Storage Temperature                               | °F              | -40.0000                                        |
| Storage Temperature                               | °F              | 85.0000                                         |
| Storage Relative Humidity                         | %RH             | 95.0000                                         |
| Características mecánicas                         |                 |                                                 |
| Conexión a la red                                 |                 | Por terminales : 4-25 mm <sup>2</sup> / por bus |
| Peso                                              |                 | 0.216 kg                                        |
| Normas                                            |                 |                                                 |
| Certificación                                     |                 | UL                                              |
| Código                                            |                 |                                                 |
| 480401                                            |                 |                                                 |

