




CITEL

DS50VGPVS-1000



- ▷ DC SPD for PV Systems
- VG Technology for Maximum Performance
- Zero Leakage Current
- Zero Current Working
- I_{max} : 40kA/pole at 8/20µs
- I_n : 20kA/pole at 8/20µs



Electrical Characteristics		
POWER SPD TYPE		UL1449 TYPE 1 CA
VOLTS	(V)	1000
AC/DC/DC PV/RF		DC PV
PHASE	(PH)	-
AMPS	(A)	N/A
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+85
MODES		DC+G or DC-G
MCOV	(V)	1000/1000/1000
IN		
15 impulses 8/20µs	(kA)	20
SCCR	(kA)	50
Mechanical Characteristics		
Connection to Network		By screw terminals: 4-25mm ²
TECHNOLOGY		MOV+GSG
NETWORK CONFIGURATION		3 poles, 2W+G
CONNECTION METHOD		SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG
MOUNTING		Din Rail
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts
DIMENSIONS		See diagram
Standards		
Certification		UL
UL STANDARD		UL1449 5th Edition
UL FILE NUMBER		E326289
Part number		
480361		

