


↳19" Rack Mounted Sure Protection Panel

- 12, 24 or 48 Port Configurations
- Supports All Network Types
- RJ45 on Front and 110 Block on Rear
- Designed for Individual Port Replacement
- UL497B Listed

Electrical Characteristics		
Max. DC operating voltage	Uc	7.5 Vdc
Insertion loss		< 1 dB
Max. load current @25°C	IL	750 mA
Max. capacitance	C	< 8 pF
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	500 A
Capacity Maximum	pF	<8
Telecom Discharge Current 10/1000	kA	0,1
Telecom Total Discharge Current 10/1000	kA	0,1
Telecom Discharge Current 10/1000	kA	0,1
Telecom Discharge Current 10/1000	kA	0,1
Option		
RFI Filter		no
Installation		
Wiring type		Shielded RJ45
Operating Temperature _{Min}	°C	-40.0000
Operating Temperature _{Max}	°C	85.0000
Operating Temperature _{Min}	°F	-40.0000
Operating Temperature _{Max}	°F	85.0000
Operating Relative Humidity _{Max}	%RH	95
Operating Altitude _{Min}	Ft	2000.0000
Operating Altitude _{Max}	Ft	6500.0000
Housing/Enclosure material		Aluminum
Mounting		19" Rack
IP Environmental rating _{IP}		IP20
NEMA Environmental rating _{NEMA}		NEMA 1
Installation Location		Indoor
Product Dimension _H	mm	89.0000
Product Dimension _W	mm	483.0000
Product Dimension _H	In	3.5000
Product Dimension _W	In	19.0000
Miscellaneous		
Individual Pack		Yes
Storage Temperature _{Min}	°C	-40.0000
Storage Temperature _{Max}	°C	85.0000
Storage Temperature _{Min}	°F	-40.0000
Storage Temperature _{Max}	°F	85.0000
Storage Relative Humidity _{Max}	%RH	95.0000
Installation		
Cable type		Ethernet
Mechanical Characteristics		
Connection to Network		Self-stripping connector 110 back/RJ45 Female. front
Part number		
6252		