



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x-8/20us)
- 5kA I_{mp} (2x-10/350us)
- 5kA I_n (10x-8/20us)
- Modular
- 2W+SHIELD+G



	<table border="1"> <thead> <tr> <th colspan="2">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Network</td> <td>4-20 mA</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>U_c 28 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max. > 3 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>I_L 300 mA</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>I_{imp} 5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>I_n 5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td>4.7 Ohm</td> </tr> <tr> <td>DATA SPD TYPE</td> <td>UL497B LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V) 24</td> </tr> <tr> <td>WIRES</td> <td>2W+Shield+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A) 0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C) -40</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C) +85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V) 40</td> </tr> <tr> <td>MCOV</td> <td>(V) 28</td> </tr> <tr> <td>I_N 10 impulses 8/20µs</td> <td>(kA) 5</td> </tr> <tr> <td>I_{MAX} 8/20µs</td> <td>(kA) 20</td> </tr> <tr> <td>I_{imp} 10/350µs</td> <td>(kA) 5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps) 10/100</td> </tr> <tr> <td>FREQUENCY</td> <td>(MHz) 3</td> </tr> <tr> <td>INSERTION LOSS (@ FREQ)</td> <td>(db) < 1</td> </tr> <tr> <td>CAPACITANCE</td> <td>(pF) < 50</td> </tr> </tbody> </table>	Electrical Characteristics		Network	4-20 mA	Max. DC operating voltage	U _c 28 Vdc	Max. frequency	f max. > 3 MHz	Max. load current @25°C	I _L 300 mA	Impulse current 2 x 10/350µs Test - D1 Category	I _{imp} 5 kA	Nominal discharge current C2 Category	I _n 5 kA	Line resistance (± 10%)	4.7 Ohm	DATA SPD TYPE	UL497B LISTED	VOLTS	(V) 24	WIRES	2W+Shield+G	LINE CURRENT MAX	(A) 0.3	AMBIENT MIN	(C) -40	AMBIENT MAX	(C) +85	RESIDUAL VOLTAGE	(V) 40	MCOV	(V) 28	I _N 10 impulses 8/20µs	(kA) 5	I _{MAX} 8/20µs	(kA) 20	I _{imp} 10/350µs	(kA) 5	DATA SPEED	(Mbps) 10/100	FREQUENCY	(MHz) 3	INSERTION LOSS (@ FREQ)	(db) < 1	CAPACITANCE	(pF) < 50
Electrical Characteristics																																															
Network	4-20 mA																																														
Max. DC operating voltage	U _c 28 Vdc																																														
Max. frequency	f max. > 3 MHz																																														
Max. load current @25°C	I _L 300 mA																																														
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp} 5 kA																																														
Nominal discharge current C2 Category	I _n 5 kA																																														
Line resistance (± 10%)	4.7 Ohm																																														
DATA SPD TYPE	UL497B LISTED																																														
VOLTS	(V) 24																																														
WIRES	2W+Shield+G																																														
LINE CURRENT MAX	(A) 0.3																																														
AMBIENT MIN	(C) -40																																														
AMBIENT MAX	(C) +85																																														
RESIDUAL VOLTAGE	(V) 40																																														
MCOV	(V) 28																																														
I _N 10 impulses 8/20µs	(kA) 5																																														
I _{MAX} 8/20µs	(kA) 20																																														
I _{imp} 10/350µs	(kA) 5																																														
DATA SPEED	(Mbps) 10/100																																														
FREQUENCY	(MHz) 3																																														
INSERTION LOSS (@ FREQ)	(db) < 1																																														
CAPACITANCE	(pF) < 50																																														
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <thead> <tr> <th colspan="2">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Technology</td> <td>GDT+Clamping diode</td> </tr> <tr> <td>Connection to Network</td> <td>By screw terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td>Plug-in DIN box</td> </tr> <tr> <td>Failsafe mode</td> <td>Short-circuit</td> </tr> <tr> <td>TECHNOLOGY</td> <td>SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td>1 Channel (2W+SHIELD+G)</td> </tr> <tr> <td>CONNECTION METHOD</td> <td>Screw terminal</td> </tr> <tr> <td>MOUNTING</td> <td>Din rail</td> </tr> <tr> <td>MATERIAL</td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td>DLAM-24D3</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">Standards</th> </tr> </thead> <tbody> <tr> <td>Certification</td> <td>UL Listed</td> </tr> <tr> <td>UL STANDARD</td> <td>UL497B</td> </tr> <tr> <td>UL CATEGORY</td> <td>QVGQ</td> </tr> <tr> <td>UL FILE NUMBER</td> <td>E184939</td> </tr> <tr> <td>STANDARDS</td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td>ROHS</td> </tr> </tbody> </table> <p>Part number 6403011</p>	Mechanical Characteristics		Technology	GDT+Clamping diode	Connection to Network	By screw terminal: cross section 0.5-2.5mm ²	Format	Plug-in DIN box	Failsafe mode	Short-circuit	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)	CONNECTION METHOD	Screw terminal	MOUNTING	Din rail	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAM-24D3	Standards		Certification	UL Listed	UL STANDARD	UL497B	UL CATEGORY	QVGQ	UL FILE NUMBER	E184939	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS				
Mechanical Characteristics																																															
Technology	GDT+Clamping diode																																														
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																																														
Format	Plug-in DIN box																																														
Failsafe mode	Short-circuit																																														
TECHNOLOGY	SAD-GDT																																														
NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)																																														
CONNECTION METHOD	Screw terminal																																														
MOUNTING	Din rail																																														
MATERIAL	Thermoplastic UL94-V0																																														
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																														
DIMENSIONS	See diagram																																														
WEIGHT	0.30 lbs																																														
SPARE PART	DLAM-24D3																																														
Standards																																															
Certification	UL Listed																																														
UL STANDARD	UL497B																																														
UL CATEGORY	QVGQ																																														
UL FILE NUMBER	E184939																																														
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																														
ENVIRONMENTAL STANDARDS	ROHS																																														

