



Electrical Characteristics

POWER SPD TYPE		UL1449 TYPE 1/2 LISTED
VOLTS	[V]	347/600
AC/DC/DC PV/RF		AC
PHASE	[PH]	3Y
AMPS	[A]	-
AMBIENT MIN	[C]	-35
AMBIENT MAX	[C]	85
MODES		L-L, L-N, L-G, N-G
VPR	[V]	3000/1800/1800/1800
MCOV	[V]	1100/550/550/550
IN(15 impulses 8/20µs)	[kA]	20
IMAX(8/20µs)	[kA]	132

Mechanical Characteristics

TECHNOLOGY		Multi-TMOV
NETWORK CONFIGURATION		3PH, 4W+G, Wye
CONNECTION METHOD		36" #10 AWG LEADS
MOUNTING		FLANGE MOUNT
MATERIAL		Polycarbonate
NEMA RATING (IP RATING)		4X
FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required
REAL-TIME DIAGNOSTICS		LED. Optional audible alarm and remote contacts.
DIMENSIONS		See diagram (mm)
WEIGHT		6 lbs

Standards

UL STANDARD		UL1449 4th Edition
UL CATEGORY		VZCA, VZCA7
UL FILE NUMBER		E326289
STANDARDS		NOM-003-SCFI-2014
ENVIRONMENTAL STANDARDS		ROHS

Part number

891821

