



Electrical Characteristics		
POWER SPD TYPE		UL1449 TYPE 2 LISTED
VOLTS	[V]	120/208
AC/DC/DC PV/RF		AC
PHASE	[PH]	3Y
AMPS	[A]	n/a
AMBIENT MIN	[C]	-
AMBIENT MAX	[C]	-
MODES		L-L, L-N, L-G, N-G
VPR	[V]	1800/800/900/800
MCOV	[V]	300/150/150/150
IN(15 impulses 8/20µs)	[kA]	5
IMAX(8/20µs)	[kA]	200
Mechanical Characteristics		
TECHNOLOGY		MOV
NETWORK CONFIGURATION		3PH, 4W+G, Wye
CONNECTION METHOD		36" #10 AWG LEADS
MOUNTING		FLANGE MOUNT
MATERIAL		Carbon steel
NEMA RATING (IP RATING)		1/12
FAIL-SAFE BEHAVIOR		30A upstream overcurrent device
REAL-TIME DIAGNOSTICS		LED, audible alarm and remote contacts.
DIMENSIONS		See diagram (mm)
WEIGHT		8 lbs
Standards		
UL STANDARD		UL1449 4th Edition
UL CATEGORY		VZCA, VZCA7
UL FILE NUMBER		E326289
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Part number		
89072277		

