



- Hybrid MOV-GSG Technology
- UL1449 Type 1 LISTED
- 50kA Surge Current Rating per mode
- Extended life with no leakage current
- Visual LED fault indicator and audible alarm
- NEMA 6 (exceeds NEMA 4X or 4)
- Optional Type 2 LISTED with UL1283 Filter
- 10-Year warranty

Electrical Characteristics		
POWER SPD TYPE		-
VOLTS	[V]	347/600
AC/DC/DC PV/RF		AC
PHASE	[PH]	3Y
AMPS	[A]	n/a
AMBIENT MIN	[C]	-35
AMBIENT MAX	[C]	+80
MODES		L-L, L-N, L-G, N-G
VPR	[V]	2500/1200/1500/1200
MCOV	[V]	560/320/320/280
IN(15 impulses 8/20µs)	[kA]	20
SCCR	[kA]	150
Mechanical Characteristics		
TECHNOLOGY		MOV-GSG
NETWORK CONFIGURATION		3PH, 4W+G, Wye
CONNECTION METHOD		3/6" #12 AWG LEADS
MOUNTING		SIDE MOUNT, THREADED M22 [1/4" NPT ADAPTER]
MATERIAL		Aluminum cast
NEMA RATING (IP RATING)		6 (IP66)
FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required
REAL-TIME DIAGNOSTICS		LED and audible alarm
DIMENSIONS		See diagram (mm)
WEIGHT		2.4 lbs
Standards		
UL STANDARD		UL1449 4th Edition
UL CATEGORY		VZCA
UL FILE NUMBER		E326289
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Part number		
89751601		

