



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x 8/20 μ s)
- 5kA I_{mp} (2x 10/350 μ s)
- 5kA I_n (10x 8/20 μ s)
- Modular with Visual Fault Indicator
- Spring & Screw Terminal versions
- Common/Differential Mode Protection

	Electrical Characteristics																																																							
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D: Clamping diode Vi: Indicator</p>	<table border="1"> <tr> <td>Max. DC operating voltage</td> <td>U_c</td> <td>28 Vdc</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Protection mode(s)</td> <td></td> <td>Common mode</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>I_{imp}</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>I_n</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category</td> <td>I_n L/PE</td> <td>5 kA</td> </tr> <tr> <td>DATA SPD TYPE</td> <td></td> <td>UL497B LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V)</td> <td>24</td> </tr> <tr> <td>WIRES</td> <td></td> <td>2W+Shield+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A)</td> <td>0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-40</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V)</td> <td>40</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>28</td> </tr> <tr> <td>I_N 10 impulses 8/20μs</td> <td>(kA)</td> <td>5</td> </tr> <tr> <td>I_{MAX} 8/20μs</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>I_{imp} 10/350μs</td> <td>(kA)</td> <td>5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps)</td> <td>10/100</td> </tr> </table>		Max. DC operating voltage	U _c	28 Vdc	Insertion loss		< 1 dB	Protection mode(s)		Common mode	Impulse current 2 x 10/350 μ s Test - D1 Category	I _{imp}	5 kA	Nominal discharge current C2 Category	I _n	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20 μ s Test x 10 - C2 Category	I _n L/PE	5 kA	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	24	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	40	MCOV	(V)	28	I _N 10 impulses 8/20 μ s	(kA)	5	I _{MAX} 8/20 μ s	(kA)	20	I _{imp} 10/350 μ s	(kA)	5	DATA SPEED	(Mbps)	10/100
Max. DC operating voltage	U _c	28 Vdc																																																						
Insertion loss		< 1 dB																																																						
Protection mode(s)		Common mode																																																						
Impulse current 2 x 10/350 μ s Test - D1 Category	I _{imp}	5 kA																																																						
Nominal discharge current C2 Category	I _n	5 kA																																																						
Nominal Discharge Current, X-C (Line/Earth) 8/20 μ s Test x 10 - C2 Category	I _n L/PE	5 kA																																																						
DATA SPD TYPE		UL497B LISTED																																																						
VOLTS	(V)	24																																																						
WIRES		2W+Shield+G																																																						
LINE CURRENT MAX	(A)	0.3																																																						
AMBIENT MIN	(C)	-40																																																						
AMBIENT MAX	(C)	+85																																																						
RESIDUAL VOLTAGE	(V)	40																																																						
MCOV	(V)	28																																																						
I _N 10 impulses 8/20 μ s	(kA)	5																																																						
I _{MAX} 8/20 μ s	(kA)	20																																																						
I _{imp} 10/350 μ s	(kA)	5																																																						
DATA SPEED	(Mbps)	10/100																																																						
<p>Connection ribbons available:</p> <table border="1"> <thead> <tr> <th>Nb of pole</th> <th>Ref. Ribbon</th> </tr> </thead> <tbody> <tr> <td>2 - 5</td> <td>R-BUS 5P (301134)</td> </tr> <tr> <td>6 - 10</td> <td>R-BUS 10P (301133)</td> </tr> <tr> <td>11 - 25</td> <td>R-BUS 25P (301135)</td> </tr> <tr> <td>26 - 49</td> <td>R-BUS 49P (301143)</td> </tr> </tbody> </table>	Nb of pole	Ref. Ribbon	2 - 5	R-BUS 5P (301134)	6 - 10	R-BUS 10P (301133)	11 - 25	R-BUS 25P (301135)	26 - 49	R-BUS 49P (301143)	Mechanical Characteristics																																													
Nb of pole	Ref. Ribbon																																																							
2 - 5	R-BUS 5P (301134)																																																							
6 - 10	R-BUS 10P (301133)																																																							
11 - 25	R-BUS 25P (301135)																																																							
26 - 49	R-BUS 49P (301143)																																																							
	<table border="1"> <tr> <td>Connection to Network</td> <td></td> <td>By spring contact terminal</td> </tr> <tr> <td>With line cut-off in case of removal plug-in module</td> <td></td> <td>Yes</td> </tr> <tr> <td>TECHNOLOGY</td> <td></td> <td>SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td></td> <td>1 pair</td> </tr> <tr> <td>CONNECTION METHOD</td> <td></td> <td>Spring Contact Terminal</td> </tr> <tr> <td>MOUNTING</td> <td></td> <td>DIN RAIL</td> </tr> <tr> <td>MATERIAL</td> <td></td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td></td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td></td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td></td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td></td> <td>DLASM-24D3</td> </tr> </table>		Connection to Network		By spring contact terminal	With line cut-off in case of removal plug-in module		Yes	TECHNOLOGY		SAD-GDT	NETWORK CONFIGURATION		1 pair	CONNECTION METHOD		Spring Contact Terminal	MOUNTING		DIN RAIL	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram	WEIGHT		0.30 lbs	SPARE PART		DLASM-24D3																					
Connection to Network		By spring contact terminal																																																						
With line cut-off in case of removal plug-in module		Yes																																																						
TECHNOLOGY		SAD-GDT																																																						
NETWORK CONFIGURATION		1 pair																																																						
CONNECTION METHOD		Spring Contact Terminal																																																						
MOUNTING		DIN RAIL																																																						
MATERIAL		Thermoplastic UL94-V0																																																						
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																																						
DIMENSIONS		See diagram																																																						
WEIGHT		0.30 lbs																																																						
SPARE PART		DLASM-24D3																																																						
	Standards																																																							
	<table border="1"> <tr> <td>UL STANDARD</td> <td></td> <td>UL497B (pending)</td> </tr> <tr> <td>UL CATEGORY</td> <td></td> <td>QVGQ</td> </tr> <tr> <td>UL FILE NUMBER</td> <td></td> <td>E184939</td> </tr> <tr> <td>STANDARDS</td> <td></td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td></td> <td>ROHS</td> </tr> </table>		UL STANDARD		UL497B (pending)	UL CATEGORY		QVGQ	UL FILE NUMBER		E184939	STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS																																							
UL STANDARD		UL497B (pending)																																																						
UL CATEGORY		QVGQ																																																						
UL FILE NUMBER		E184939																																																						
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																						
ENVIRONMENTAL STANDARDS		ROHS																																																						
	Part number																																																							
	6419034																																																							

