



- VG Technology
- UL1449 Type 4CA
- 50kA Surge Current Rating
- Visual fault indicator and remote contacts
- 10-Year warranty



	Electrical Characteristics																																													
	<table border="1"> <tr> <td>Network</td> <td></td> <td>230/400 V 3-phase+N</td> </tr> <tr> <td>Total Maximum discharge current <i>max. total withstand @ 8/20 μs</i></td> <td>I_{max} Total</td> <td>200 kA</td> </tr> <tr> <td>POWER SPD TYPE</td> <td></td> <td>UL1449 5th Ed. TYPE 4CA</td> </tr> <tr> <td>VOLTS</td> <td>(V)</td> <td>480/277</td> </tr> <tr> <td>AC/DC/DC PV/RF</td> <td></td> <td>AC</td> </tr> <tr> <td>PHASE</td> <td>(PH)</td> <td>3Y</td> </tr> <tr> <td>AMPS</td> <td>(A)</td> <td>N/A</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-40</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+85</td> </tr> <tr> <td>MODES</td> <td></td> <td>L-L, L-N, L-G, N-G</td> </tr> <tr> <td>MLV</td> <td>(V)</td> <td>6720/3360/3360/3360</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>610/305/305/305</td> </tr> <tr> <td>IN</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>SCCR</td> <td>(kA)</td> <td>n/a</td> </tr> <tr> <td>IMAX <i>8/20μs</i></td> <td>(kA)</td> <td>50</td> </tr> </table>		Network		230/400 V 3-phase+N	Total Maximum discharge current <i>max. total withstand @ 8/20 μs</i>	I _{max} Total	200 kA	POWER SPD TYPE		UL1449 5th Ed. TYPE 4CA	VOLTS	(V)	480/277	AC/DC/DC PV/RF		AC	PHASE	(PH)	3Y	AMPS	(A)	N/A	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	MODES		L-L, L-N, L-G, N-G	MLV	(V)	6720/3360/3360/3360	MCOV	(V)	610/305/305/305	IN	(kA)	20	SCCR	(kA)	n/a	IMAX <i>8/20μs</i>	(kA)
Network		230/400 V 3-phase+N																																												
Total Maximum discharge current <i>max. total withstand @ 8/20 μs</i>	I _{max} Total	200 kA																																												
POWER SPD TYPE		UL1449 5th Ed. TYPE 4CA																																												
VOLTS	(V)	480/277																																												
AC/DC/DC PV/RF		AC																																												
PHASE	(PH)	3Y																																												
AMPS	(A)	N/A																																												
AMBIENT MIN	(C)	-40																																												
AMBIENT MAX	(C)	+85																																												
MODES		L-L, L-N, L-G, N-G																																												
MLV	(V)	6720/3360/3360/3360																																												
MCOV	(V)	610/305/305/305																																												
IN	(kA)	20																																												
SCCR	(kA)	n/a																																												
IMAX <i>8/20μs</i>	(kA)	50																																												
<p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	Mechanical Characteristics																																													
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>VG Technology (MOV+GSG)</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminals: 2.5-25mm² (35mm² rigid)</td> </tr> <tr> <td>Format</td> <td></td> <td>Plug-in modular box</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Disconnection from AC network</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.360 kg</td> </tr> <tr> <td>TECHNOLOGY</td> <td></td> <td>MOV-GSG</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td></td> <td>4 pole, 4W+G, 3PH Wye</td> </tr> <tr> <td>CONNECTION METHOD</td> <td></td> <td>Screw Terminal (4-13AWG)</td> </tr> <tr> <td>MOUNTING</td> <td></td> <td>Din Rail</td> </tr> <tr> <td>MATERIAL</td> <td></td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td></td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>FAIL-SAFE BEHAVIOR</td> <td></td> <td>Disconnection via fuse-link</td> </tr> <tr> <td>REAL-TIME DIAGNOSTICS</td> <td></td> <td>Visual indicator and remote contacts</td> </tr> <tr> <td>DIMENSIONS</td> <td></td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td></td> <td>0.79 lbs</td> </tr> </table>		Technology		VG Technology (MOV+GSG)	Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)	Format		Plug-in modular box	Failsafe mode		Disconnection from AC network	Weight		0.360 kg	TECHNOLOGY		MOV-GSG	NETWORK CONFIGURATION		4 pole, 4W+G, 3PH Wye	CONNECTION METHOD		Screw Terminal (4-13AWG)	MOUNTING		Din Rail	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	FAIL-SAFE BEHAVIOR		Disconnection via fuse-link	REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts	DIMENSIONS		See diagram	WEIGHT	
Technology		VG Technology (MOV+GSG)																																												
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)																																												
Format		Plug-in modular box																																												
Failsafe mode		Disconnection from AC network																																												
Weight		0.360 kg																																												
TECHNOLOGY		MOV-GSG																																												
NETWORK CONFIGURATION		4 pole, 4W+G, 3PH Wye																																												
CONNECTION METHOD		Screw Terminal (4-13AWG)																																												
MOUNTING		Din Rail																																												
MATERIAL		Thermoplastic UL94-V0																																												
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																												
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link																																												
REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts																																												
DIMENSIONS		See diagram																																												
WEIGHT		0.79 lbs																																												
Standards																																														
Certification		UL Recognized																																												
UL STANDARD		UL1449 5th Edition																																												
UL CATEGORY		VZCA2																																												
UL FILE NUMBER		E326289																																												
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993																																												
ENVIRONMENTAL STANDARDS		ROHS																																												
Part number																																														
821130224553																																														

