





# UL TYPE 4CA - I<sub>max</sub> 50kA - I<sub>n</sub> 20kA - Modular

# CITEL

## DAC54VGUS-480DCT



- VG Technology
- UL1449 Type 4CA
- 50kA Surge Current Rating
- Visual fault indicator and remote contacts
- 10-Year warranty



### Características eléctricas

POWER SPD TYPE		UL1449 5th Ed. TYPE 4CA
TENSION	(V)	480/240
AC/DC/DC PV/RF		AC
FASE	(PH)	3H
AMPS	(A)	N/A
AMBIENT MIN	(C)	-40
AMBIENT MAX	(C)	+85
MODOS		L-L, L-N, L-G, N-G, H-L, H-N, H-G
MLV	(V)	6720/3360/3360/3310/8440/4220/4220
MCOV	(V)	610/150/305/305/815/510/510
IN	(kA)	20
I <sub>cc cortocircuito</sub>	(kA)	n/a
IMAX	(kA)	50

### Características mecánicas

TECNOLOGIA		MOV-GSG
CONFIGURACION DE RED		4 pole, 4W+G, Hi-Leg Delta
FORMA DE CONEXION		Screw Terminal (4-13AWG)
MONTAJE		Din Rail
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
DESCONEXION SEGURA		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts
DIMENSIONS		See diagram
WEIGHT		0.79 lbs

### Normas

UL STANDARD		UL1449 5th Edition
UL CATEGORY		VZCA2
UL FILE NUMBER		E326289
NORMAS		NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS

### Código

821130224555

