



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x-8/20us)
- 5kA I_{imp} (2x-10/350us)
- 5kA I_n (10x-8/20us)
- Modular
- 2W+SHIELD+G



	<table border="1"> <thead> <tr> <th colspan="2">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>DATA SPD TYPE</td> <td>UL Listed for Hazardous Locations</td> </tr> <tr> <td>VOLTS</td> <td>(V) 12</td> </tr> <tr> <td>WIRES</td> <td>2W+Shield+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A) 0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C) -40</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C) +85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V) 30</td> </tr> <tr> <td>MCOV</td> <td>(V) 15</td> </tr> <tr> <td>IN</td> <td>(kA) 5</td> </tr> <tr> <td>10 impulses 8/20μs</td> <td></td> </tr> <tr> <td>IMAX</td> <td>(kA) 20</td> </tr> <tr> <td>8/20μs</td> <td></td> </tr> <tr> <td>I_{imp}</td> <td>(kA) 5</td> </tr> <tr> <td>10/350μs</td> <td></td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps) 10/100</td> </tr> <tr> <td>FREQUENCY</td> <td>(MHz) >3</td> </tr> <tr> <td>INSERTION LOSS (@ FREQ)</td> <td>(db) < 1</td> </tr> <tr> <td>CAPACITANCE</td> <td>(pF) < 50</td> </tr> </tbody> </table>	Electrical Characteristics		DATA SPD TYPE	UL Listed for Hazardous Locations	VOLTS	(V) 12	WIRES	2W+Shield+G	LINE CURRENT MAX	(A) 0.3	AMBIENT MIN	(C) -40	AMBIENT MAX	(C) +85	RESIDUAL VOLTAGE	(V) 30	MCOV	(V) 15	IN	(kA) 5	10 impulses 8/20μs		IMAX	(kA) 20	8/20μs		I _{imp}	(kA) 5	10/350μs		DATA SPEED	(Mbps) 10/100	FREQUENCY	(MHz) >3	INSERTION LOSS (@ FREQ)	(db) < 1	CAPACITANCE	(pF) < 50
Electrical Characteristics																																							
DATA SPD TYPE	UL Listed for Hazardous Locations																																						
VOLTS	(V) 12																																						
WIRES	2W+Shield+G																																						
LINE CURRENT MAX	(A) 0.3																																						
AMBIENT MIN	(C) -40																																						
AMBIENT MAX	(C) +85																																						
RESIDUAL VOLTAGE	(V) 30																																						
MCOV	(V) 15																																						
IN	(kA) 5																																						
10 impulses 8/20μs																																							
IMAX	(kA) 20																																						
8/20μs																																							
I _{imp}	(kA) 5																																						
10/350μs																																							
DATA SPEED	(Mbps) 10/100																																						
FREQUENCY	(MHz) >3																																						
INSERTION LOSS (@ FREQ)	(db) < 1																																						
CAPACITANCE	(pF) < 50																																						
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <thead> <tr> <th colspan="2">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>TECHNOLOGY</td> <td>SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td>1 Channel (2W+SHIELD+G)</td> </tr> <tr> <td>CONNECTION METHOD</td> <td>Screw terminal</td> </tr> <tr> <td>MOUNTING</td> <td>Din rail</td> </tr> <tr> <td>MATERIAL</td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td>DLAM-12D3</td> </tr> </tbody> </table>	Mechanical Characteristics		TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)	CONNECTION METHOD	Screw terminal	MOUNTING	Din rail	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAM-12D3																		
Mechanical Characteristics																																							
TECHNOLOGY	SAD-GDT																																						
NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)																																						
CONNECTION METHOD	Screw terminal																																						
MOUNTING	Din rail																																						
MATERIAL	Thermoplastic UL94-V0																																						
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																						
DIMENSIONS	See diagram																																						
WEIGHT	0.30 lbs																																						
SPARE PART	DLAM-12D3																																						
<table border="1"> <thead> <tr> <th colspan="2">Standards</th> </tr> </thead> </table>		Standards																																					
Standards																																							
<table border="1"> <tbody> <tr> <td>Certification</td> <td>UL Listed</td> </tr> <tr> <td>UL STANDARD</td> <td>UL497B & UL121201 Hazardous Location</td> </tr> <tr> <td>UL CATEGORY</td> <td>QVGQ & QVSI</td> </tr> <tr> <td>UL FILE NUMBER</td> <td>E184939 & E527349</td> </tr> <tr> <td>UL121201 HAZARDOUS LOCATION</td> <td>Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5</td> </tr> <tr> <td>STANDARDS</td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td>ROHS</td> </tr> </tbody> </table>		Certification	UL Listed	UL STANDARD	UL497B & UL121201 Hazardous Location	UL CATEGORY	QVGQ & QVSI	UL FILE NUMBER	E184939 & E527349	UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																								
Certification	UL Listed																																						
UL STANDARD	UL497B & UL121201 Hazardous Location																																						
UL CATEGORY	QVGQ & QVSI																																						
UL FILE NUMBER	E184939 & E527349																																						
UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																						
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																						
ENVIRONMENTAL STANDARDS	ROHS																																						
<table border="1"> <thead> <tr> <th colspan="2">Part number</th> </tr> </thead> <tbody> <tr> <td colspan="2">897012</td> </tr> </tbody> </table>		Part number		897012																																			
Part number																																							
897012																																							

