



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x-8/20us)
- 5kA I_{imp} (2x-10/350us)
- 5kA I_n (10x-8/20us)
- Modular
- 2W+SHIELD+G



	Electrical Characteristics																																																										
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Line resistance (± 10%)</td><td></td><td>4.7 Ohm</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL Listed for Hazardous Locations</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>12</td></tr> <tr><td>WIRES</td><td></td><td>2W+Shield+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-40</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>30</td></tr> <tr><td>MCOV</td><td>(V)</td><td>15</td></tr> <tr><td>IN</td><td></td><td></td></tr> <tr><td>10 impulses 8/20µs</td><td>(kA)</td><td>5</td></tr> <tr><td>IMAX</td><td></td><td></td></tr> <tr><td>8/20µs</td><td>(kA)</td><td>20</td></tr> <tr><td>I_{imp}</td><td></td><td></td></tr> <tr><td>10/350µs</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>FREQUENCY</td><td>(MHz)</td><td>>3</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>< 1</td></tr> <tr><td>CAPACITANCE</td><td>(pF)</td><td>< 50</td></tr> </table>		Line resistance (± 10%)		4.7 Ohm	DATA SPD TYPE		UL Listed for Hazardous Locations	VOLTS	(V)	12	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	30	MCOV	(V)	15	IN			10 impulses 8/20µs	(kA)	5	IMAX			8/20µs	(kA)	20	I _{imp}			10/350µs	(kA)	5	DATA SPEED	(Mbps)	10/100	FREQUENCY	(MHz)	>3	INSERTION LOSS (@ FREQ)	(db)	< 1	CAPACITANCE	(pF)	< 50
Line resistance (± 10%)		4.7 Ohm																																																									
DATA SPD TYPE		UL Listed for Hazardous Locations																																																									
VOLTS	(V)	12																																																									
WIRES		2W+Shield+G																																																									
LINE CURRENT MAX	(A)	0.3																																																									
AMBIENT MIN	(C)	-40																																																									
AMBIENT MAX	(C)	+85																																																									
RESIDUAL VOLTAGE	(V)	30																																																									
MCOV	(V)	15																																																									
IN																																																											
10 impulses 8/20µs	(kA)	5																																																									
IMAX																																																											
8/20µs	(kA)	20																																																									
I _{imp}																																																											
10/350µs	(kA)	5																																																									
DATA SPEED	(Mbps)	10/100																																																									
FREQUENCY	(MHz)	>3																																																									
INSERTION LOSS (@ FREQ)	(db)	< 1																																																									
CAPACITANCE	(pF)	< 50																																																									
	Mechanical Characteristics																																																										
	<table border="1"> <tr><td>Failsafe mode</td><td>Short-circuit</td></tr> <tr><td>TECHNOLOGY</td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td>1 Channel (2W+SHIELD+G)</td></tr> <tr><td>CONNECTION METHOD</td><td>Screw terminal</td></tr> <tr><td>MOUNTING</td><td>Din rail</td></tr> <tr><td>MATERIAL</td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td>DLAM-12D3</td></tr> </table>	Failsafe mode	Short-circuit	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)	CONNECTION METHOD	Screw terminal	MOUNTING	Din rail	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAM-12D3																																						
Failsafe mode	Short-circuit																																																										
TECHNOLOGY	SAD-GDT																																																										
NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)																																																										
CONNECTION METHOD	Screw terminal																																																										
MOUNTING	Din rail																																																										
MATERIAL	Thermoplastic UL94-V0																																																										
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																																										
DIMENSIONS	See diagram																																																										
WEIGHT	0.30 lbs																																																										
SPARE PART	DLAM-12D3																																																										
	Standards																																																										
	<table border="1"> <tr><td>Certification</td><td>UL Listed</td></tr> <tr><td>UL STANDARD</td><td>UL497B & UL121201 Hazardous Location</td></tr> <tr><td>UL CATEGORY</td><td>QVQG & QVSI</td></tr> <tr><td>UL FILE NUMBER</td><td>E184939 & E527349</td></tr> <tr><td>UL121201 HAZARDOUS LOCATION</td><td>Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5</td></tr> <tr><td>STANDARDS</td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td>ROHS</td></tr> </table>	Certification	UL Listed	UL STANDARD	UL497B & UL121201 Hazardous Location	UL CATEGORY	QVQG & QVSI	UL FILE NUMBER	E184939 & E527349	UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																																												
Certification	UL Listed																																																										
UL STANDARD	UL497B & UL121201 Hazardous Location																																																										
UL CATEGORY	QVQG & QVSI																																																										
UL FILE NUMBER	E184939 & E527349																																																										
UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																																										
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																										
ENVIRONMENTAL STANDARDS	ROHS																																																										
	Part number																																																										
	897012																																																										

