



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I<sub>max</sub> (1x-8/20us)
- 5kA I<sub>mp</sub> (2x-10/350us)
- 5kA I<sub>n</sub> (10x-8/20us)
- Modular
- 2W+SHIELD+G



	<table border="1"> <thead> <tr> <th colspan="3">Características eléctricas</th> </tr> </thead> <tbody> <tr> <td>DATA SPD TYPE</td> <td></td> <td>UL Listed for Hazardous Locations</td> </tr> <tr> <td>TENSION</td> <td>(V)</td> <td>12</td> </tr> <tr> <td>WIRES</td> <td></td> <td>2W+Shield+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A)</td> <td>0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-40</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V)</td> <td>30</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>15</td> </tr> <tr> <td>IN</td> <td>(kA)</td> <td>5</td> </tr> <tr> <td>IMAX</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>I<sub>imp</sub></td> <td>(kA)</td> <td>5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps)</td> <td>10/100</td> </tr> <tr> <td>FREQUENCY</td> <td>(MHz)</td> <td>&gt;3</td> </tr> <tr> <td>INSERTION LOSS (@ FREQ)</td> <td>(db)</td> <td>&lt; 1</td> </tr> <tr> <td>CAPACITANCE</td> <td>(pF)</td> <td>&lt; 50</td> </tr> </tbody> </table>	Características eléctricas			DATA SPD TYPE		UL Listed for Hazardous Locations	TENSION	(V)	12	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	30	MCOV	(V)	15	IN	(kA)	5	IMAX	(kA)	20	I <sub>imp</sub>	(kA)	5	DATA SPEED	(Mbps)	10/100	FREQUENCY	(MHz)	>3	INSERTION LOSS (@ FREQ)	(db)	< 1	CAPACITANCE	(pF)	< 50
Características eléctricas																																																	
DATA SPD TYPE		UL Listed for Hazardous Locations																																															
TENSION	(V)	12																																															
WIRES		2W+Shield+G																																															
LINE CURRENT MAX	(A)	0.3																																															
AMBIENT MIN	(C)	-40																																															
AMBIENT MAX	(C)	+85																																															
RESIDUAL VOLTAGE	(V)	30																																															
MCOV	(V)	15																																															
IN	(kA)	5																																															
IMAX	(kA)	20																																															
I <sub>imp</sub>	(kA)	5																																															
DATA SPEED	(Mbps)	10/100																																															
FREQUENCY	(MHz)	>3																																															
INSERTION LOSS (@ FREQ)	(db)	< 1																																															
CAPACITANCE	(pF)	< 50																																															
<p>G : Descargador tripolar  Gb : Descargador bipolar  R : Resistor  D : Diodo limitador</p>	<table border="1"> <thead> <tr> <th colspan="3">Características mecánicas</th> </tr> </thead> <tbody> <tr> <td>TECNOLOGIA</td> <td></td> <td>SAD-GDT</td> </tr> <tr> <td>CONFIGURACION DE RED</td> <td></td> <td>1 Channel (2W+SHIELD+G)</td> </tr> <tr> <td>FORMA DE CONEXION</td> <td></td> <td>Screw terminal</td> </tr> <tr> <td>MONTAJE</td> <td></td> <td>Din rail</td> </tr> <tr> <td>MATERIAL</td> <td></td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td></td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td></td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td></td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td></td> <td>DLAM-12D3</td> </tr> </tbody> </table>	Características mecánicas			TECNOLOGIA		SAD-GDT	CONFIGURACION DE RED		1 Channel (2W+SHIELD+G)	FORMA DE CONEXION		Screw terminal	MONTAJE		Din rail	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram	WEIGHT		0.30 lbs	SPARE PART		DLAM-12D3																		
Características mecánicas																																																	
TECNOLOGIA		SAD-GDT																																															
CONFIGURACION DE RED		1 Channel (2W+SHIELD+G)																																															
FORMA DE CONEXION		Screw terminal																																															
MONTAJE		Din rail																																															
MATERIAL		Thermoplastic UL94-V0																																															
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																															
DIMENSIONS		See diagram																																															
WEIGHT		0.30 lbs																																															
SPARE PART		DLAM-12D3																																															
	<table border="1"> <thead> <tr> <th colspan="3">Normas</th> </tr> </thead> <tbody> <tr> <td>Certificación</td> <td></td> <td>UL Listed</td> </tr> <tr> <td>UL STANDARD</td> <td></td> <td>UL497B &amp; UL121201 Hazardous Location</td> </tr> <tr> <td>UL CATEGORY</td> <td></td> <td>QVGG &amp; QVSI</td> </tr> <tr> <td>UL FILE NUMBER</td> <td></td> <td>E184939 &amp; E527349</td> </tr> <tr> <td>UL121201 HAZARDOUS LOCATION</td> <td></td> <td>Class I, Division 2, Groups A, B, C &amp; D: Operating. Temp. T5</td> </tr> <tr> <td>NORMAS</td> <td></td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td></td> <td>ROHS</td> </tr> <tr> <td><b>Código</b></td> <td></td> <td><b>897012</b></td> </tr> </tbody> </table>	Normas			Certificación		UL Listed	UL STANDARD		UL497B & UL121201 Hazardous Location	UL CATEGORY		QVGG & QVSI	UL FILE NUMBER		E184939 & E527349	UL121201 HAZARDOUS LOCATION		Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	NORMAS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS	<b>Código</b>		<b>897012</b>																					
Normas																																																	
Certificación		UL Listed																																															
UL STANDARD		UL497B & UL121201 Hazardous Location																																															
UL CATEGORY		QVGG & QVSI																																															
UL FILE NUMBER		E184939 & E527349																																															
UL121201 HAZARDOUS LOCATION		Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																															
NORMAS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																															
ENVIRONMENTAL STANDARDS		ROHS																																															
<b>Código</b>		<b>897012</b>																																															

