



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x-8/20us)
- 5kA I_{imp} (2x-10/350us)
- 5kA I_n (10x-8/20us)
- Modular
- 2W+SHIELD+G



	<table border="1"> <thead> <tr> <th colspan="2">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Line resistance (± 10%)</td> <td>4.7 Ohm</td> </tr> <tr> <td>DATA SPD TYPE</td> <td>UL Listed for Hazardous Locations</td> </tr> <tr> <td>VOLTS</td> <td>(V) 24</td> </tr> <tr> <td>WIRES</td> <td>2W+Shield+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A) 0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C) -40</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C) +85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V) 40</td> </tr> <tr> <td>MCOV</td> <td>(V) 28</td> </tr> <tr> <td>IN</td> <td>(kA) 5</td> </tr> <tr> <td>10 impulses 8/20µs</td> <td>(kA) 5</td> </tr> <tr> <td>IMAX</td> <td>(kA) 20</td> </tr> <tr> <td>8/20µs</td> <td>(kA) 20</td> </tr> <tr> <td>I_{imp}</td> <td>(kA) 5</td> </tr> <tr> <td>10/350µs</td> <td>(kA) 5</td> </tr> </tbody> </table>	Electrical Characteristics		Line resistance (± 10%)	4.7 Ohm	DATA SPD TYPE	UL Listed for Hazardous Locations	VOLTS	(V) 24	WIRES	2W+Shield+G	LINE CURRENT MAX	(A) 0.3	AMBIENT MIN	(C) -40	AMBIENT MAX	(C) +85	RESIDUAL VOLTAGE	(V) 40	MCOV	(V) 28	IN	(kA) 5	10 impulses 8/20µs	(kA) 5	IMAX	(kA) 20	8/20µs	(kA) 20	I _{imp}	(kA) 5	10/350µs	(kA) 5
Electrical Characteristics																																	
Line resistance (± 10%)	4.7 Ohm																																
DATA SPD TYPE	UL Listed for Hazardous Locations																																
VOLTS	(V) 24																																
WIRES	2W+Shield+G																																
LINE CURRENT MAX	(A) 0.3																																
AMBIENT MIN	(C) -40																																
AMBIENT MAX	(C) +85																																
RESIDUAL VOLTAGE	(V) 40																																
MCOV	(V) 28																																
IN	(kA) 5																																
10 impulses 8/20µs	(kA) 5																																
IMAX	(kA) 20																																
8/20µs	(kA) 20																																
I _{imp}	(kA) 5																																
10/350µs	(kA) 5																																
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <thead> <tr> <th colspan="2">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Failsafe mode</td> <td>Short-circuit</td> </tr> <tr> <td>TECHNOLOGY</td> <td>SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td>1 Channel (2W+SHIELD+G)</td> </tr> <tr> <td>CONNECTION METHOD</td> <td>Screw terminal</td> </tr> <tr> <td>MOUNTING</td> <td>Din rail</td> </tr> <tr> <td>MATERIAL</td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td>DLAM-24D3</td> </tr> </tbody> </table>	Mechanical Characteristics		Failsafe mode	Short-circuit	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)	CONNECTION METHOD	Screw terminal	MOUNTING	Din rail	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAM-24D3										
Mechanical Characteristics																																	
Failsafe mode	Short-circuit																																
TECHNOLOGY	SAD-GDT																																
NETWORK CONFIGURATION	1 Channel (2W+SHIELD+G)																																
CONNECTION METHOD	Screw terminal																																
MOUNTING	Din rail																																
MATERIAL	Thermoplastic UL94-V0																																
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																
DIMENSIONS	See diagram																																
WEIGHT	0.30 lbs																																
SPARE PART	DLAM-24D3																																
	<table border="1"> <thead> <tr> <th colspan="2">Standards</th> </tr> </thead> <tbody> <tr> <td>Certification</td> <td>UL Listed</td> </tr> <tr> <td>UL STANDARD</td> <td>UL497B & UL121201 Hazardous Location</td> </tr> <tr> <td>UL CATEGORY</td> <td>QVGG & QVSI</td> </tr> <tr> <td>UL FILE NUMBER</td> <td>E184939 & E527349</td> </tr> <tr> <td>UL121201 HAZARDOUS LOCATION</td> <td>Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5</td> </tr> <tr> <td>STANDARDS</td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td>ROHS</td> </tr> <tr> <td>Part number</td> <td>897014</td> </tr> </tbody> </table>	Standards		Certification	UL Listed	UL STANDARD	UL497B & UL121201 Hazardous Location	UL CATEGORY	QVGG & QVSI	UL FILE NUMBER	E184939 & E527349	UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS	Part number	897014														
Standards																																	
Certification	UL Listed																																
UL STANDARD	UL497B & UL121201 Hazardous Location																																
UL CATEGORY	QVGG & QVSI																																
UL FILE NUMBER	E184939 & E527349																																
UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																
ENVIRONMENTAL STANDARDS	ROHS																																
Part number	897014																																

