



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max} (1x-8/20us)
- ↳ 5kA I_{mp} (2x-10/350us)
- ↳ 5kA I_n (10x-8/20us)
- ↳ Modular
- ↳ 2W+SHIELD+G



	<table border="1"> <thead> <tr> <th colspan="3">Características eléctricas</th> </tr> </thead> <tbody> <tr> <td>DATA SPD TYPE</td> <td></td> <td>UL Listed for Hazardous Locations</td> </tr> <tr> <td>TENSION</td> <td>(V)</td> <td>24</td> </tr> <tr> <td>WIRES</td> <td></td> <td>2W+Shield+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A)</td> <td>0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-40</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V)</td> <td>40</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>28</td> </tr> <tr> <td>IN</td> <td>(kA)</td> <td>5</td> </tr> <tr> <td>IMAX</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>I_{imp}</td> <td>(kA)</td> <td>5</td> </tr> </tbody> </table>	Características eléctricas			DATA SPD TYPE		UL Listed for Hazardous Locations	TENSION	(V)	24	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	40	MCOV	(V)	28	IN	(kA)	5	IMAX	(kA)	20	I _{imp}	(kA)	5																		
Características eléctricas																																																							
DATA SPD TYPE		UL Listed for Hazardous Locations																																																					
TENSION	(V)	24																																																					
WIRES		2W+Shield+G																																																					
LINE CURRENT MAX	(A)	0.3																																																					
AMBIENT MIN	(C)	-40																																																					
AMBIENT MAX	(C)	+85																																																					
RESIDUAL VOLTAGE	(V)	40																																																					
MCOV	(V)	28																																																					
IN	(kA)	5																																																					
IMAX	(kA)	20																																																					
I _{imp}	(kA)	5																																																					
<p>G : Descargador tripolar Gb : Descargador bipolar R : Resistor D : Diodo limitador</p>	<table border="1"> <thead> <tr> <th colspan="3">Características mecánicas</th> </tr> </thead> <tbody> <tr> <td>TECNOLOGIA</td> <td></td> <td>SAD-GDT</td> </tr> <tr> <td>CONFIGURACION DE RED</td> <td></td> <td>1 Channel (2W+SHIELD+G)</td> </tr> <tr> <td>FORMA DE CONEXION</td> <td></td> <td>Screw terminal</td> </tr> <tr> <td>MONTAJE</td> <td></td> <td>Din rail</td> </tr> <tr> <td>MATERIAL</td> <td></td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td></td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td></td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td></td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td></td> <td>DLAM-24D3</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="3">Normas</th> </tr> </thead> <tbody> <tr> <td>Certificación</td> <td></td> <td>UL Listed</td> </tr> <tr> <td>UL STANDARD</td> <td></td> <td>UL497B & UL121201 Hazardous Location</td> </tr> <tr> <td>UL CATEGORY</td> <td></td> <td>QVGG & QVSI</td> </tr> <tr> <td>UL FILE NUMBER</td> <td></td> <td>E184939 & E527349</td> </tr> <tr> <td>UL121201 HAZARDOUS LOCATION</td> <td></td> <td>Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5</td> </tr> <tr> <td>NORMAS</td> <td></td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td></td> <td>ROHS</td> </tr> </tbody> </table> <p>Código 897014</p>	Características mecánicas			TECNOLOGIA		SAD-GDT	CONFIGURACION DE RED		1 Channel (2W+SHIELD+G)	FORMA DE CONEXION		Screw terminal	MONTAJE		Din rail	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram	WEIGHT		0.30 lbs	SPARE PART		DLAM-24D3	Normas			Certificación		UL Listed	UL STANDARD		UL497B & UL121201 Hazardous Location	UL CATEGORY		QVGG & QVSI	UL FILE NUMBER		E184939 & E527349	UL121201 HAZARDOUS LOCATION		Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	NORMAS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS
Características mecánicas																																																							
TECNOLOGIA		SAD-GDT																																																					
CONFIGURACION DE RED		1 Channel (2W+SHIELD+G)																																																					
FORMA DE CONEXION		Screw terminal																																																					
MONTAJE		Din rail																																																					
MATERIAL		Thermoplastic UL94-V0																																																					
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																																					
DIMENSIONS		See diagram																																																					
WEIGHT		0.30 lbs																																																					
SPARE PART		DLAM-24D3																																																					
Normas																																																							
Certificación		UL Listed																																																					
UL STANDARD		UL497B & UL121201 Hazardous Location																																																					
UL CATEGORY		QVGG & QVSI																																																					
UL FILE NUMBER		E184939 & E527349																																																					
UL121201 HAZARDOUS LOCATION		Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																																					
NORMAS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																					
ENVIRONMENTAL STANDARDS		ROHS																																																					

