



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x-8/20us)
- 5kA I_{imp} (2x-10/350us)
- 5kA I_n (10x-8/20us)
- Modular
- 2W+SHIELD+G



	Electrical Characteristics																																																										
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Line resistance (± 10%)</td><td></td><td>4.7 Ohm</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL Listed for Hazardous Locations</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>48</td></tr> <tr><td>WIRES</td><td></td><td>2W+Shield+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-40</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>70</td></tr> <tr><td>MCOV</td><td>(V)</td><td>60</td></tr> <tr><td>IN</td><td>(kA)</td><td>5</td></tr> <tr><td>10 impulses 8/20µs</td><td></td><td></td></tr> <tr><td>IMAX</td><td>(kA)</td><td>20</td></tr> <tr><td>8/20µs</td><td></td><td></td></tr> <tr><td>I_{imp}</td><td>(kA)</td><td>5</td></tr> <tr><td>10/350µs</td><td></td><td></td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>FREQUENCY</td><td>(MHz)</td><td>up to 10</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>< 1</td></tr> <tr><td>CAPACITANCE</td><td>(pF)</td><td>< 50</td></tr> </table>		Line resistance (± 10%)		4.7 Ohm	DATA SPD TYPE		UL Listed for Hazardous Locations	VOLTS	(V)	48	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	70	MCOV	(V)	60	IN	(kA)	5	10 impulses 8/20µs			IMAX	(kA)	20	8/20µs			I _{imp}	(kA)	5	10/350µs			DATA SPEED	(Mbps)	10/100	FREQUENCY	(MHz)	up to 10	INSERTION LOSS (@ FREQ)	(db)	< 1	CAPACITANCE	(pF)	< 50
Line resistance (± 10%)		4.7 Ohm																																																									
DATA SPD TYPE		UL Listed for Hazardous Locations																																																									
VOLTS	(V)	48																																																									
WIRES		2W+Shield+G																																																									
LINE CURRENT MAX	(A)	0.3																																																									
AMBIENT MIN	(C)	-40																																																									
AMBIENT MAX	(C)	+85																																																									
RESIDUAL VOLTAGE	(V)	70																																																									
MCOV	(V)	60																																																									
IN	(kA)	5																																																									
10 impulses 8/20µs																																																											
IMAX	(kA)	20																																																									
8/20µs																																																											
I _{imp}	(kA)	5																																																									
10/350µs																																																											
DATA SPEED	(Mbps)	10/100																																																									
FREQUENCY	(MHz)	up to 10																																																									
INSERTION LOSS (@ FREQ)	(db)	< 1																																																									
CAPACITANCE	(pF)	< 50																																																									
	Mechanical Characteristics																																																										
	<table border="1"> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>TECHNOLOGY</td><td></td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td></td><td>1 Channel (2W+SHIELD+G)</td></tr> <tr><td>CONNECTION METHOD</td><td></td><td>Screw terminal</td></tr> <tr><td>MOUNTING</td><td></td><td>Din rail</td></tr> <tr><td>MATERIAL</td><td></td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td></td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td></td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td></td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td></td><td>DLAM-48D3</td></tr> </table>		Failsafe mode		Short-circuit	TECHNOLOGY		SAD-GDT	NETWORK CONFIGURATION		1 Channel (2W+SHIELD+G)	CONNECTION METHOD		Screw terminal	MOUNTING		Din rail	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram	WEIGHT		0.30 lbs	SPARE PART		DLAM-48D3																											
Failsafe mode		Short-circuit																																																									
TECHNOLOGY		SAD-GDT																																																									
NETWORK CONFIGURATION		1 Channel (2W+SHIELD+G)																																																									
CONNECTION METHOD		Screw terminal																																																									
MOUNTING		Din rail																																																									
MATERIAL		Thermoplastic UL94-V0																																																									
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																																									
DIMENSIONS		See diagram																																																									
WEIGHT		0.30 lbs																																																									
SPARE PART		DLAM-48D3																																																									
	Standards																																																										
	<table border="1"> <tr><td>Certification</td><td></td><td>UL Listed</td></tr> <tr><td>UL STANDARD</td><td></td><td>UL497B & UL121201 Hazardous Location</td></tr> <tr><td>UL CATEGORY</td><td></td><td>QVQG & QVSI</td></tr> <tr><td>UL FILE NUMBER</td><td></td><td>E184939 & E527349</td></tr> <tr><td>UL121201 HAZARDOUS LOCATION</td><td></td><td>Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5</td></tr> <tr><td>STANDARDS</td><td></td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td></td><td>ROHS</td></tr> </table>		Certification		UL Listed	UL STANDARD		UL497B & UL121201 Hazardous Location	UL CATEGORY		QVQG & QVSI	UL FILE NUMBER		E184939 & E527349	UL121201 HAZARDOUS LOCATION		Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS																																				
Certification		UL Listed																																																									
UL STANDARD		UL497B & UL121201 Hazardous Location																																																									
UL CATEGORY		QVQG & QVSI																																																									
UL FILE NUMBER		E184939 & E527349																																																									
UL121201 HAZARDOUS LOCATION		Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																																									
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																									
ENVIRONMENTAL STANDARDS		ROHS																																																									
	Part number																																																										
	897013																																																										

