



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max} (1x-8/20us)
- ↳ 5kA I_{mp} (2x-10/350us)
- ↳ 5kA I_n (10x-8/20us)
- ↳ Modular
- ↳ 2W+SHIELD+G



	<table border="1"> <thead> <tr> <th colspan="2">Características eléctricas</th> </tr> </thead> <tbody> <tr> <td>DATA SPD TYPE</td> <td>UL Listed for Hazardous Locations</td> </tr> <tr> <td>TENSION</td> <td>(V) 48</td> </tr> <tr> <td>WIRES</td> <td>2W+Shield+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A) 0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C) -40</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C) +85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V) 70</td> </tr> <tr> <td>MCOV</td> <td>(V) 60</td> </tr> <tr> <td>IN</td> <td>(kA) 5</td> </tr> <tr> <td>IMAX</td> <td>(kA) 20</td> </tr> <tr> <td>I_{imp}</td> <td>(kA) 5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps) 10/100</td> </tr> <tr> <td>FREQUENCY</td> <td>(MHz) up to 10</td> </tr> <tr> <td>INSERTION LOSS (@ FREQ)</td> <td>(db) < 1</td> </tr> <tr> <td>CAPACITANCE</td> <td>(pF) < 50</td> </tr> </tbody> </table>	Características eléctricas		DATA SPD TYPE	UL Listed for Hazardous Locations	TENSION	(V) 48	WIRES	2W+Shield+G	LINE CURRENT MAX	(A) 0.3	AMBIENT MIN	(C) -40	AMBIENT MAX	(C) +85	RESIDUAL VOLTAGE	(V) 70	MCOV	(V) 60	IN	(kA) 5	IMAX	(kA) 20	I _{imp}	(kA) 5	DATA SPEED	(Mbps) 10/100	FREQUENCY	(MHz) up to 10	INSERTION LOSS (@ FREQ)	(db) < 1	CAPACITANCE	(pF) < 50
Características eléctricas																																	
DATA SPD TYPE	UL Listed for Hazardous Locations																																
TENSION	(V) 48																																
WIRES	2W+Shield+G																																
LINE CURRENT MAX	(A) 0.3																																
AMBIENT MIN	(C) -40																																
AMBIENT MAX	(C) +85																																
RESIDUAL VOLTAGE	(V) 70																																
MCOV	(V) 60																																
IN	(kA) 5																																
IMAX	(kA) 20																																
I _{imp}	(kA) 5																																
DATA SPEED	(Mbps) 10/100																																
FREQUENCY	(MHz) up to 10																																
INSERTION LOSS (@ FREQ)	(db) < 1																																
CAPACITANCE	(pF) < 50																																
<p>G : Descargador tripolar Gb : Descargador bipolar R : Resistor D : Diodo limitador</p>	<table border="1"> <thead> <tr> <th colspan="2">Características mecánicas</th> </tr> </thead> <tbody> <tr> <td>TECNOLOGIA</td> <td>SAD-GDT</td> </tr> <tr> <td>CONFIGURACION DE RED</td> <td>1 Channel (2W+SHIELD+G)</td> </tr> <tr> <td>FORMA DE CONEXION</td> <td>Screw terminal</td> </tr> <tr> <td>MONTAJE</td> <td>Din rail</td> </tr> <tr> <td>MATERIAL</td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td>DLAM-48D3</td> </tr> </tbody> </table>	Características mecánicas		TECNOLOGIA	SAD-GDT	CONFIGURACION DE RED	1 Channel (2W+SHIELD+G)	FORMA DE CONEXION	Screw terminal	MONTAJE	Din rail	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAM-48D3												
Características mecánicas																																	
TECNOLOGIA	SAD-GDT																																
CONFIGURACION DE RED	1 Channel (2W+SHIELD+G)																																
FORMA DE CONEXION	Screw terminal																																
MONTAJE	Din rail																																
MATERIAL	Thermoplastic UL94-V0																																
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																
DIMENSIONS	See diagram																																
WEIGHT	0.30 lbs																																
SPARE PART	DLAM-48D3																																
	<table border="1"> <thead> <tr> <th colspan="2">Normas</th> </tr> </thead> <tbody> <tr> <td>Certificación</td> <td>UL Listed</td> </tr> <tr> <td>UL STANDARD</td> <td>UL497B & UL121201 Hazardous Location</td> </tr> <tr> <td>UL CATEGORY</td> <td>QVGG & QVSI</td> </tr> <tr> <td>UL FILE NUMBER</td> <td>E184939 & E527349</td> </tr> <tr> <td>UL121201 HAZARDOUS LOCATION</td> <td>Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5</td> </tr> <tr> <td>NORMAS</td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td>ROHS</td> </tr> </tbody> </table> <p>Código 897013</p>	Normas		Certificación	UL Listed	UL STANDARD	UL497B & UL121201 Hazardous Location	UL CATEGORY	QVGG & QVSI	UL FILE NUMBER	E184939 & E527349	UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	NORMAS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																
Normas																																	
Certificación	UL Listed																																
UL STANDARD	UL497B & UL121201 Hazardous Location																																
UL CATEGORY	QVGG & QVSI																																
UL FILE NUMBER	E184939 & E527349																																
UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																
NORMAS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																
ENVIRONMENTAL STANDARDS	ROHS																																

