



M50-120T-A-RA



- ↳ Hybrid MOV-GSG Technology
- ↳ UL1449 Type 1 LISTED
- ↳ 50kA Surge Current Rating per mode
- ↳ Extended life with no leakage current
- ↳ Visual LED fault indicator, audible alarm & remote contacts
- ↳ NEMA 6 (exceeds NEMA 4X or 4)
- ↳ 10-Year warranty

	<b>Electrical Characteristics</b>																																														
	<table border="1"> <tr> <td>POWER SPD TYPE</td> <td></td> <td>UL1449 TYPE 1 LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V)</td> <td>240/120</td> </tr> <tr> <td>AC/DC/DC PV/RF</td> <td></td> <td>AC</td> </tr> <tr> <td>PHASE</td> <td>(PH)</td> <td>1S</td> </tr> <tr> <td>AMPS</td> <td>(A)</td> <td>N/A</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-35</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+80</td> </tr> <tr> <td>MODES</td> <td></td> <td>L-L, L-N, L-G, N-G</td> </tr> <tr> <td>VPR</td> <td>(V)</td> <td>1200/700/1200/1200</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>280/140/140/120</td> </tr> <tr> <td>IN</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>15 impulses 8/20<math>\mu</math>s</td> <td></td> <td></td> </tr> <tr> <td>SCCR</td> <td>(kA)</td> <td>150</td> </tr> <tr> <td>IMAX</td> <td>(kA)</td> <td>50</td> </tr> <tr> <td>8/20<math>\mu</math>s</td> <td></td> <td></td> </tr> </table>		POWER SPD TYPE		UL1449 TYPE 1 LISTED	VOLTS	(V)	240/120	AC/DC/DC PV/RF		AC	PHASE	(PH)	1S	AMPS	(A)	N/A	AMBIENT MIN	(C)	-35	AMBIENT MAX	(C)	+80	MODES		L-L, L-N, L-G, N-G	VPR	(V)	1200/700/1200/1200	MCOV	(V)	280/140/140/120	IN	(kA)	20	15 impulses 8/20 $\mu$ s			SCCR	(kA)	150	IMAX	(kA)	50	8/20 $\mu$ s		
POWER SPD TYPE		UL1449 TYPE 1 LISTED																																													
VOLTS	(V)	240/120																																													
AC/DC/DC PV/RF		AC																																													
PHASE	(PH)	1S																																													
AMPS	(A)	N/A																																													
AMBIENT MIN	(C)	-35																																													
AMBIENT MAX	(C)	+80																																													
MODES		L-L, L-N, L-G, N-G																																													
VPR	(V)	1200/700/1200/1200																																													
MCOV	(V)	280/140/140/120																																													
IN	(kA)	20																																													
15 impulses 8/20 $\mu$ s																																															
SCCR	(kA)	150																																													
IMAX	(kA)	50																																													
8/20 $\mu$ s																																															
<b>Mechanical Characteristics</b>																																															
<table border="1"> <tr> <td>Weight</td> <td>0.945 kg</td> </tr> <tr> <td>TECHNOLOGY</td> <td>MOV-GSG</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td>1PH, 3W+G, Split Phase</td> </tr> <tr> <td>CONNECTION METHOD</td> <td>3/6" #12 AWG LEADS</td> </tr> <tr> <td>MOUNTING</td> <td>SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER)</td> </tr> <tr> <td>MATERIAL</td> <td>Aluminum cast</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td>6 (IP66)</td> </tr> <tr> <td>FAIL-SAFE BEHAVIOR</td> <td>Yes, no upstream over current protection required</td> </tr> <tr> <td>REAL-TIME DIAGNOSTICS</td> <td>LED, audible alarm and remote contacts</td> </tr> <tr> <td>REMOTE CONTACT CONNECTION</td> <td>NO/NC-Wire 3ft, 22 Ga.</td> </tr> <tr> <td>DIMENSIONS</td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td>2.5 lbs.</td> </tr> </table>		Weight	0.945 kg	TECHNOLOGY	MOV-GSG	NETWORK CONFIGURATION	1PH, 3W+G, Split Phase	CONNECTION METHOD	3/6" #12 AWG LEADS	MOUNTING	SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER)	MATERIAL	Aluminum cast	NEMA RATING (IP RATING)	6 (IP66)	FAIL-SAFE BEHAVIOR	Yes, no upstream over current protection required	REAL-TIME DIAGNOSTICS	LED, audible alarm and remote contacts	REMOTE CONTACT CONNECTION	NO/NC-Wire 3ft, 22 Ga.	DIMENSIONS	See diagram	WEIGHT	2.5 lbs.																						
Weight	0.945 kg																																														
TECHNOLOGY	MOV-GSG																																														
NETWORK CONFIGURATION	1PH, 3W+G, Split Phase																																														
CONNECTION METHOD	3/6" #12 AWG LEADS																																														
MOUNTING	SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER)																																														
MATERIAL	Aluminum cast																																														
NEMA RATING (IP RATING)	6 (IP66)																																														
FAIL-SAFE BEHAVIOR	Yes, no upstream over current protection required																																														
REAL-TIME DIAGNOSTICS	LED, audible alarm and remote contacts																																														
REMOTE CONTACT CONNECTION	NO/NC-Wire 3ft, 22 Ga.																																														
DIMENSIONS	See diagram																																														
WEIGHT	2.5 lbs.																																														
<b>Standards</b>																																															
<table border="1"> <tr> <td>UL STANDARD</td> <td>UL1449 5th Edition</td> </tr> <tr> <td>UL CATEGORY</td> <td>VZCA</td> </tr> <tr> <td>UL FILE NUMBER</td> <td>E326289</td> </tr> <tr> <td>STANDARDS</td> <td>NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td>ROHS</td> </tr> </table>		UL STANDARD	UL1449 5th Edition	UL CATEGORY	VZCA	UL FILE NUMBER	E326289	STANDARDS	NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																																				
UL STANDARD	UL1449 5th Edition																																														
UL CATEGORY	VZCA																																														
UL FILE NUMBER	E326289																																														
STANDARDS	NOM-003-SCFI-2014, NOM-001-SCFI-1993																																														
ENVIRONMENTAL STANDARDS	ROHS																																														
<b>Part number</b>																																															
751106																																															