



M50-120T-A-RA



- ↳ Hybrid MOV-GSG Technology
- ↳ UL1449 Type 1 LISTED
- ↳ 50kA Surge Current Rating per mode
- ↳ Extended life with no leakage current
- ↳ Visual LED fault indicator, audible alarm & remote contacts
- ↳ NEMA 6 (exceeds NEMA 4X or 4)
- ↳ 10-Year warranty

	Características eléctricas																																								
	<table border="1"> <tr> <td>POWER SPD TYPE</td> <td></td> <td>UL1449 TYPE 1 LISTED</td> </tr> <tr> <td>TENSION</td> <td>(V)</td> <td>240/120</td> </tr> <tr> <td>AC/DC/DC PV/RF</td> <td></td> <td>AC</td> </tr> <tr> <td>FASE</td> <td>(PH)</td> <td>1S</td> </tr> <tr> <td>AMPS</td> <td>(A)</td> <td>N/A</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-35</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+80</td> </tr> <tr> <td>MODOS</td> <td></td> <td>L-L, L-N, L-G, N-G</td> </tr> <tr> <td>VPR</td> <td>(V)</td> <td>1200/700/1200/1200</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>280/140/140/120</td> </tr> <tr> <td>IN</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>I_{cc cortocircuito}</td> <td>(kA)</td> <td>150</td> </tr> <tr> <td>IMAX</td> <td>(kA)</td> <td>50</td> </tr> </table>		POWER SPD TYPE		UL1449 TYPE 1 LISTED	TENSION	(V)	240/120	AC/DC/DC PV/RF		AC	FASE	(PH)	1S	AMPS	(A)	N/A	AMBIENT MIN	(C)	-35	AMBIENT MAX	(C)	+80	MODOS		L-L, L-N, L-G, N-G	VPR	(V)	1200/700/1200/1200	MCOV	(V)	280/140/140/120	IN	(kA)	20	I _{cc cortocircuito}	(kA)	150	IMAX	(kA)	50
POWER SPD TYPE		UL1449 TYPE 1 LISTED																																							
TENSION	(V)	240/120																																							
AC/DC/DC PV/RF		AC																																							
FASE	(PH)	1S																																							
AMPS	(A)	N/A																																							
AMBIENT MIN	(C)	-35																																							
AMBIENT MAX	(C)	+80																																							
MODOS		L-L, L-N, L-G, N-G																																							
VPR	(V)	1200/700/1200/1200																																							
MCOV	(V)	280/140/140/120																																							
IN	(kA)	20																																							
I _{cc cortocircuito}	(kA)	150																																							
IMAX	(kA)	50																																							
Características mecánicas																																									
		0.945 kg																																							
		MOV-GSG																																							
		1PH, 3W+G, Split Phase																																							
		36" #12 AWG LEADS																																							
		SIDE MOUNT, THREADED M22 (1/4" NPT ADAPTER)																																							
		Aluminum cast																																							
		6 (IP66)																																							
		Yes, no upstream over current protection required																																							
		LED, audible alarm and remote contacts																																							
		NO/NC-Wire 3ft, 22 Ga.																																							
		See diagram																																							
		2.5 lbs.																																							
Normas																																									
		UL1449 5th Edition																																							
		VZCA																																							
		E326289																																							
		NOM-003-SCFI-2014, NOM-001-SCFI-1993																																							
		ROHS																																							
Código																																									
751106																																									