




CITEL

B280-48DBC



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I<sub>max</sub>
- ↳ 5kA I<sub>mp</sub>
- ↳ 5kA I<sub>n</sub>



Características eléctricas			
Tensión DC máx. de operación	Uc		53 Vdc
Perdida de inserción			< 1 dB
Modo(s) de protección			Modo Común o Mode Diferenciado
DATA SPD TYPE			UL497B LISTED
TENSION	(V)		48
WIRES			4W+GROUND
LINE CURRENT MAX	(A)		0.3
AMBIENT MIN	(C)		-50
AMBIENT MAX	(C)		+85
RESIDUAL VOLTAGE	(V)		20
MCOV	(V)		60/72/72
IN	(kA)		5
IMAX	(kA)		20
I <sub>imp</sub>	(kA)		5
DATA SPEED	(Mbps)		10/100/1000
Características mecánicas			
Conexión a la red			Por tornillos : sección mini/máxi 0.4-1.5 mm <sup>2</sup>
Peso			0.043 kg
TECNOLOGIA			SAD-GDT
CONFIGURACION DE RED			4W+G
FORMA DE CONEXION			RJ11 Connector
MONTAJE			Wall mount
MATERIAL			Thermoplastic UL94-V0
NEMA RATING (IP RATING)			NEMA 2 (IP20)
DIMENSIONS			See diagram
WEIGHT			0.30 lbs
SPARE PART			n/a
Normas			
Certificación			UL 497B
UL STANDARD			UL497B
UL CATEGORY			QVGQ
UL FILE NUMBER			E184939
NORMAS			IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS			ROHS
Código			
72754			

