



- ↳ Cat. 5,5E and Cat. 6 Surge Protector
- ↳ Hybrid GDT and Diode Technology
- ↳ 10/100/1000Mbps Compatible
- ↳ Bi-Directional Protection
- ↳ Shielded Connector Configurations
- ↳ DIN Rail, Screw Lug, and Flange Mounting
- ↳ UL497B Listed

Características eléctricas		
Perdida de inserción		< 1 dB
Corriente máx. De línea @25°C	IL	1000 mA
Capacidad máx.	C	< 25 pF
Corriente de choque <i>Prueba 10/350µs x 2 - categoría D1</i>	limp	500 A
Instalación		
Operating Temperature	°C	-40.0000
Operating Temperature	°C	85.0000
Operating Temperature	°F	-40.0000
Operating Temperature	°F	85.0000
Operating Relative Humidity	%RH	95
Operating Altitude	Ft	2000.0000
Operating Altitude	Ft	6500.0000
Housing/Enclosure material		Aluminum
Mounting		Flange
IP Environmental rating		IP20
Installation Location		indoor
Product Dimension	mm	44.0000
Product Dimension	mm	54.0000
Product Dimension	mm	34.0000
Product Dimension	In	1.7300
Product Dimension	In	2.1200
Product Dimension	In	1.3300
Miscelánea		
Individual Pack		Yes
Storage Temperature	°C	-40.0000
Storage Temperature	°C	85.0000
Storage Temperature	°F	-40.0000
Storage Temperature	°F	85.0000
Instalación		
Cable type		Ethernet
Características mecánicas		
Peso		0.117 kg
Código		
560303		

