


**↳19" Rack Mounted Sure Protection Panel**

- 12, 24 or 48 Port Configurations
- Supports All Network Types
- RJ45 on Front and 110 Block on Rear
- Designed for Individual Port Replacement
- UL497B Listed

<b>Características eléctricas</b>		
Tensión DC máx. de operación	Uc	60 Vdc
Perdida de inserción		< 1 dB
Corriente máx. De línea @25°C	IL	750 mA
Capacidad máx.	C	< 8 pF (lignes ethernet)
Corriente de descarga nominal X-C (Línea/Tierra) <i>Prueba 8/20µs x 10 - categoria C2</i>	In L/PE	250 A
Capacity	pF	<8
Telecom Discharge Current	kA	0,05
Telecom Total Discharge Current	kA	0,05
Telecom Discharge Current	kA	0,05
Telecom Discharge Current	kA	0,05
<b>Opción</b>		
RFI Filter		no
<b>Instalación</b>		
Wiring type		Shielded RJ45
Operating Temperature	°C	-40.0000
Operating Temperature	°C	85.0000
Operating Temperature	°F	-40.0000
Operating Temperature	°F	85.0000
Operating Relative Humidity	%RH	95
Operating Altitude	Ft	2000.0000
Operating Altitude	Ft	6500.0000
Housing/Enclosure material		Aluminum
Mounting		19" Rack
IP Environmental rating		IP20
NEMA Environmental rating		NEMA 1
Installation Location		Indoor
Product Dimension	mm	89.0000
Product Dimension	mm	483.0000
Product Dimension	In	3.5000
Product Dimension	In	19.0000
<b>Miscelánea</b>		
Individual Pack		Yes
Storage Temperature	°C	-40.0000
Storage Temperature	°C	85.0000
Storage Temperature	°F	-40.0000
Storage Temperature	°F	85.0000
Storage Relative Humidity	%RH	95.0000
<b>Instalación</b>		
Cable type		Ethernet
<b>Características mecánicas</b>		
Conexión a la red		Conector 110 punchdown entrada/RJ45 Hembra salida
Peso		0.3 kg
<b>Código</b>		
6273		