



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max} (1x-8/20us)
- 5kA I_{mp} (2x-10/350us)
- 5kA I_n (10x-8/20us)
- Modular
- 2W+SHIELD+G



	<p>Electrical Characteristics</p>																																																												
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Max. DC operating voltage</td><td>U_c</td><td>8 Vdc</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>I_L</td><td>300 mA</td></tr> <tr><td>Impulse current 2 x 10/350µs Test - D1 Category</td><td>I_{imp}</td><td>5 kA</td></tr> <tr><td>Nominal discharge current C2 Category</td><td>I_n</td><td>5 kA</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL497B LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>6</td></tr> <tr><td>WIRES</td><td></td><td>2W+Shield+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-40</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>20</td></tr> <tr><td>MCOV</td><td>(V)</td><td>8</td></tr> <tr><td>I_N 10 impulses 8/20µs</td><td>(kA)</td><td>5</td></tr> <tr><td>I_{MAX} 8/20µs</td><td>(kA)</td><td>20</td></tr> <tr><td>I_{imp} 10/350µs</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>FREQUENCY</td><td>(MHz)</td><td>up to 10</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>< 1</td></tr> <tr><td>CAPACITANCE</td><td>(pF)</td><td>< 50</td></tr> </table>	Max. DC operating voltage	U _c	8 Vdc	Insertion loss		< 1 dB	Max. load current @25°C	I _L	300 mA	Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA	Nominal discharge current C2 Category	I _n	5 kA	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	6	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	20	MCOV	(V)	8	I _N 10 impulses 8/20µs	(kA)	5	I _{MAX} 8/20µs	(kA)	20	I _{imp} 10/350µs	(kA)	5	DATA SPEED	(Mbps)	10/100	FREQUENCY	(MHz)	up to 10	INSERTION LOSS (@ FREQ)	(db)	< 1	CAPACITANCE	(pF)	< 50
Max. DC operating voltage	U _c	8 Vdc																																																											
Insertion loss		< 1 dB																																																											
Max. load current @25°C	I _L	300 mA																																																											
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA																																																											
Nominal discharge current C2 Category	I _n	5 kA																																																											
DATA SPD TYPE		UL497B LISTED																																																											
VOLTS	(V)	6																																																											
WIRES		2W+Shield+G																																																											
LINE CURRENT MAX	(A)	0.3																																																											
AMBIENT MIN	(C)	-40																																																											
AMBIENT MAX	(C)	+85																																																											
RESIDUAL VOLTAGE	(V)	20																																																											
MCOV	(V)	8																																																											
I _N 10 impulses 8/20µs	(kA)	5																																																											
I _{MAX} 8/20µs	(kA)	20																																																											
I _{imp} 10/350µs	(kA)	5																																																											
DATA SPEED	(Mbps)	10/100																																																											
FREQUENCY	(MHz)	up to 10																																																											
INSERTION LOSS (@ FREQ)	(db)	< 1																																																											
CAPACITANCE	(pF)	< 50																																																											
	<p>Mechanical Characteristics</p>																																																												
	<table border="1"> <tr><td>Connection to Network</td><td>By screw terminal: cross section 0.5-2.5mm²</td></tr> <tr><td>Weight</td><td>0.063 kg</td></tr> <tr><td>TECHNOLOGY</td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td>1 pair</td></tr> <tr><td>CONNECTION METHOD</td><td>Screw terminal</td></tr> <tr><td>MOUNTING</td><td>Din rail</td></tr> <tr><td>MATERIAL</td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td>DLAM-06D3</td></tr> </table>	Connection to Network	By screw terminal: cross section 0.5-2.5mm ²	Weight	0.063 kg	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 pair	CONNECTION METHOD	Screw terminal	MOUNTING	Din rail	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAM-06D3																																						
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																																																												
Weight	0.063 kg																																																												
TECHNOLOGY	SAD-GDT																																																												
NETWORK CONFIGURATION	1 pair																																																												
CONNECTION METHOD	Screw terminal																																																												
MOUNTING	Din rail																																																												
MATERIAL	Thermoplastic UL94-V0																																																												
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																																												
DIMENSIONS	See diagram																																																												
WEIGHT	0.30 lbs																																																												
SPARE PART	DLAM-06D3																																																												
	<p>Standards</p>																																																												
	<table border="1"> <tr><td>Certification</td><td>UL Listed</td></tr> <tr><td>UL STANDARD</td><td>UL497B</td></tr> <tr><td>UL CATEGORY</td><td>QVGQ</td></tr> <tr><td>UL FILE NUMBER</td><td>E184939</td></tr> <tr><td>STANDARDS</td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td>ROHS</td></tr> </table>	Certification	UL Listed	UL STANDARD	UL497B	UL CATEGORY	QVGQ	UL FILE NUMBER	E184939	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																																																
Certification	UL Listed																																																												
UL STANDARD	UL497B																																																												
UL CATEGORY	QVGQ																																																												
UL FILE NUMBER	E184939																																																												
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																												
ENVIRONMENTAL STANDARDS	ROHS																																																												
	<p>Part number</p>																																																												
	<p>6401011</p>																																																												

