




- Hybrid SAD-GDT Technology
- Compact 6mm module
- UL497B LISTED
- 10kA I<sub>max</sub> (1x 8/20us)
- 2.5kA I<sub>imp</sub> (2x 10/350us)
- 5kA I<sub>n</sub> (10x 8/20us)
- 2W+SHIELD+G
- Common/Differential mode protection



Electrical Characteristics		
Network		Fipway, WorldFIP, FieldBus-h2
Max. DC operating voltage	U <sub>c</sub>	53 Vdc
Max. frequency	f max.	> 20 MHz
Insertion loss		< 1 dB
Max. load current @25°C	IL	300 mA
Impulse current 2 x 10/350µs Test - D1 Category	I <sub>imp</sub>	2.5 kA
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I <sub>n</sub> L/PE	5 kA
Line resistance (± 10%)		4.7 Ohm
DATA SPD TYPE		UL497B LISTED
VOLTS	(V)	48
WIRES		2W+Shield+G
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-50
AMBIENT MAX	(C)	+85
RESIDUAL VOLTAGE	(V)	20
MCOV	(V)	8/72/72
I <sub>N</sub> 10 impulses 8/20µs	(kA)	5
I <sub>MAX</sub> 8/20µs	(kA)	10
I <sub>imp</sub> 10/350µs	(kA)	2.5
DATA SPEED	(Mbps)	10/100/1000
FREQUENCY	(MHz)	>20
INSERTION LOSS (@ FREQ)	(db)	< 1
Mechanical Characteristics		
Technology		GDT+Clamping diode
Connection to Network		By spring terminal - max. cross section 2.5mm <sup>2</sup> / AWG 13 (solid or stranded)
Format		DIN box
Failsafe mode		Short-circuit
Weight		0.029 kg
TECHNOLOGY		SAD-GDT
NETWORK CONFIGURATION		1 pair
CONNECTION METHOD		Screw Terminal
MOUNTING		Din Rail
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
DIMENSIONS		See diagram
WEIGHT		0.30 lbs
Standards		
Certification		UL 497B
UL STANDARD		UL497B
UL CATEGORY		QVGQ
UL FILE NUMBER		E184939
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Part number		
641114		

