





CITEL

CMJ8-POE-A-C5E



P: 3-electrode GDT
DBC: Low capacitance diode

Electrical Characteristics			
Max. DC operating voltage	Uc		60 Vdc - 650 mA
Insertion loss			< 1 dB
Max. load current @25°C	IL		1200 mA
Impulse current 2 x 10/350µs Test - D1 Category	Iimp		500 A
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE		2000 A
Return Loss Minimum	db		<1
Let through Voltage at In	V		70.0000
Option			
RFI Filter			No
Installation			
Wiring type			Shielded RJ45
Operating Temperature _{Min}	°C		-40.0000
Operating Temperature _{Max}	°C		85.0000
Operating Temperature _{Min}	°F		-40.0000
Operating Temperature _{Max}	°F		85.0000
Operating Relative Humidity _{Max}	%RH		95
Operating Altitude _{Min}	Ft		2000.0000
Operating Altitude _{Max}	Ft		6500.0000
Housing/Enclosure material			Plastic
Flammability rating <i>UL 94</i>			V0
Mounting			POLE or
IP Environmental rating <i>IP</i>			IP66
Installation Location			Indoor
Spare part			PCB
Accessories			Stainless steel bracket
Product Dimension <i>L</i>	mm		140.0000
Product Dimension <i>H</i>	mm		50.0000
Product Dimension <i>W</i>	mm		113.0000
Product Dimension <i>L</i>	In		5.5100
Product Dimension <i>H</i>	In		2.0000
Product Dimension <i>W</i>	In		4.4400
Miscellaneous			
Individual Pack			Yes
Storage Temperature _{Min}	°C		-40.0000
Storage Temperature _{Max}	°C		85.0000
Storage Temperature _{Min}	°F		-40.0000
Storage Temperature _{Max}	°F		85.0000
Storage Relative Humidity _{Max}	%RH		34.0000
Installation			
Cable type			Ethernet
Mechanical Characteristics			
Connection to Network			RJ45 shielded connectors Female input/output
Weight			0.18 kg
Standards			
Certification			UL 497B
Part number			
892002			

