

# CGMJ8-POE-A-C5E



POE++ compatible

- Shielded enclosure and connectors
- 16 kA maximum surge discharge capability
- UL497B

Caractéristiques Électriques		
DATA SPD TYPE		UL497B LISTED
VOLTS	[V]	48
AC/DC/DC PV/RF		DC
WIRES		8W+Shield+Ground
LINE CURRENT MAX	[A]	1.2
POWER RATING	[W]	95
AMBIENT MIN	[C]	-35
AMBIENT MAX	[C]	+85
MODES		DC+-DC-,DC+-G,DC--G,SH-G
RESIDUAL VOLTAGE	[V]	70
MCOV	[V]	60/72/72
IN(10 impulses 8/20µs)	[kA]	10.0000
DATA SPEED	[bps]	10/100/1000
Caractéristiques Mécaniques		
TECHNOLOGY		SAD-GDT
NETWORK CONFIGURATION		Single POE Line
CONNECTION METHOD		Shielded RJ45
MOUNTING		FLANGE MOUNT/POLE MOUNT KIT
MATERIAL		Polycarbonate
FLAMMABILITY RATING		UL94-V0
NEMA RATING (IP RATING)		6 (IP66)
DIMENSIONS		See diagram
Normes		
UL STANDARD		UL497B
UL CATEGORY		QVGQ
UL FILE NUMBER		E184939
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Code article		
<b>892004</b>		