



- ↳ 19" patch panel surge protector for POE-A
- ↳ 32 ports
- ↳ In/Out front : RJ45
- ↳ Maintenance possible per port
- ↳ Secondary Protection
- ↳ UL497B

Electrical Characteristics		
Network		POE mode A, Gigabit Ethernet, POE Plus
Max. DC operating voltage	Uc	60 Vdc
Max. frequency	f max.	250 MHz
Max. data rate		10/100/1000 Mbps
Insertion loss		< 1 dB
Max. load current @25°C	IL	750 mA
Max. capacitance	C	< 25 pF (ligne ethernet)
Nominal Discharge Current, X-C (Line/Earth) <i>8/20µs Test x 10 - C2 Category</i>	In L/PE	250 A
Capacity <i>Maximum</i>	pF	<25
Telecom Discharge Current <i>10/1000</i>	kA	0,05
Telecom Total Discharge Current <i>10/1000</i>	kA	0,05
Telecom Discharge Current <i>10/1000</i>	kA	0,05
Telecom Discharge Current <i>10/1000</i>	kA	0,05
Max Discharge Current <i>Imax (8/20µs x 1)</i>	kA	0.0500
Installation		
Operating Temperature <sub>Min</sub>	°C	-40.0000
Operating Temperature <sub>Max</sub>	°C	85.0000
Operating Temperature <sub>Min</sub>	°F	-40.0000
Operating Temperature <sub>Max</sub>	°F	85.0000
Operating Relative Humidity <sub>Max</sub>	%RH	95
Operating Altitude <sub>Min</sub>	Ft	2000.0000
Operating Altitude <sub>Max</sub>	Ft	6500.0000
Housing/Enclosure material		aluminum
Mounting		Rack mount
IP Environmental rating/IP		IP20
Installation Location		indoor
Product Dimension <sub>L</sub>	mm	483.0000
Product Dimension <sub>H</sub>	mm	89.0000
Product Dimension <sub>L</sub>	In	19.0200
Product Dimension <sub>H</sub>	In	3.5040
Miscellaneous		
Individual Pack		Yes
Storage Temperature <sub>Min</sub>	°C	-40.0000
Storage Temperature <sub>Max</sub>	°C	85.0000
Storage Temperature <sub>Min</sub>	°F	-40.0000
Storage Temperature <sub>Max</sub>	°F	85.0000
Installation		
Cable type		Ethernet
Mechanical Characteristics		
Technology		Diode écrêtage
Connection to Network		RJ45 Female input/output
Format		Rack 19"
Failsafe mode		Short-circuit
Pinout		(1-2)(3-6)(4-5)(7-8)
Part number		
891104		