

# RAK32-POE-B-S0



- 19" patch panel surge protector for POE-B
- 32 ports
- In/Out front : RJ45
- Maintenance possible per port
- Secondary Protection
- UL497B



Installation		
Operating Temperature(Min)	°C	-40.0000
Operating Temperature(Max)	°C	85.0000
Operating Temperature(Min)	°F	-40.0000
Operating Temperature(Max)	°F	85.0000
Operating Relative Humidity(Max)	%RH	95
Operating Altitude(Max)	m	2000.0000
Operating Altitude(Max)	Ft	6500.0000
Housing/Enclosure material		aluminum
Mounting		Rack mount
IP Environmental rating(IP)		IP20
Installation Location		indoor
Product Dimension(L)	mm	483.0000
Product Dimension(H)	mm	89.0000
Product Dimension(L)	In	19.0200
Product Dimension(H)	In	3.5040
Miscellaneous		
Individual Pack		Yes
Storage Temperature(Min)	°C	-40.0000
Storage Temperature(Max)	°C	85.0000
Storage Temperature(Min)	°F	-40.0000
Storage Temperature(Max)	°F	85.0000
Installation		
Cable type		Ethernet
Caractéristiques Électriques		
Max. capacitance	C	< 25 pF (ligne ethernet)
Capacity(Maximum)	pF	<25
Telecom Discharge Current(10/1000)	kA	0,13
Telecom Total Discharge Current(10/1000)	kA	0,5
Telecom Discharge Current(10/1000)	kA	0,13
Telecom Discharge Current(10/1000)	kA	0,5
Caractéristiques Mécaniques		
Technology		Diode écrêtage
Dimensions		See diagram
Normes		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B / IEEE 802-3at
Code article		
<b>891105</b>		

